#### **Prime Ministers Museum and Library**

### <u>Teen Murti House</u> <u>New Delhi – 110011</u>

#### **NOTICE INVITING E-TENDER**

#### **INDEX**

Name of Work: - Annual Repair work and M/o of Library building PMML campus during 2025-26 (SH Repair and replacement of old Rusted C.I pipe line in shaft etc) Teen Murti House, New Delhi..

Sl. No.	DETAILS	PAGES
1.	Index	Page -1
2.	Notice Inviting e-tenders	Page -2
3.	C.P.W.D 6 for e-Tendering	Page 3 to 6
4.	Receipt for Deposit original EMD	Page -7
5.	Form 'F'	Page -8
6.	Information and Instructions for Contractors for e-Tendering	Page -9-10
7.	Form-7	Page-11 to 12
8.	Performa of Schedules	Page -13 to 21
9.	Scope of work	Page -22
10.	Annexure I & II	Page -23 to 24
11.	General Terms & Conditions	Page -25 to 28
12.	Special Conditions	Page -29 to 31
13.	Condition for cement and steel	Page -32 to 33
14.	Minimum Quality Assurance Plan	Page -34
15.	List of Preferred Makes	Page -35 to 38
16.	Guarantee Bond	Page -39 to 40
17.	Schedule of Quantities	Page -41 to 45

NIT No :76-16/2025-26/Admin/Engg/Procurement of Rs. 23,48,008/- (Rupees twenty three lakh forty eight thousand and eight only) having Pages No. (1 to 45) is hereby approved.

**Director** 

PMML Teen Murti Campus New Delhi

#### **NOTICE INVITING e-TENDERS**

The **Director PMML Teen Murti Campus New Delhi,** invites the online **PERCENTAGE RATE** bids from approved and eligible contractors of CPWD in appropriate class for the following work (s): -

NIT No. :- 76-16/2025-26/Admin/Engg/Procurement

Name of Work : Annual Repair work and M/o of Library building PMML

campus during 2025-26(SH Repair and replacement of old Rusted C.I pipe line in shaft etc) Teen Murti House, New

Delhi..

**Estimated Cost** :- **Rs. 23,48,008/-**

**Earnest Money :- Rs. 70,440/-**

Period of completion:- 30 Days

Last time and date of submission of tender is 05/12/2025 by 5:30 PM (within 21 days)

The tender forms and other details can be obtained from the website <a href="https://www.pmml.nic.in">https://www.pmml.nic.in</a> and <a href="https://www.nmml.ewizard.in">https://www.nmml.ewizard.in</a> and financial bids is to be submitted online through e-wizard portal.

**Director** 

PMML Teen Murti Campus New Delhi

#### **GOVERNMENT OF INDIA**

# PRIME MINISTERS MUSEUM AND LIBRARY NOTICE INVITING TENDER FOR e-TENDERING

Percentage rate bids are invited on behalf of Director PMML from approved and eligible contractor's appropriate class for the following work

Name of Work: Annual Repair work and M/o of Library building PMML campus

during 2025-26 (SH Repair and replacement of old Rusted C.I pipe

line in shaft etc) Teen Murti House, New Delhi...

The enlistment of the contractors should be valid on the last date of submission of bids.

In case the last date of submission of tender is extended, the enlistment of contractor should be valid on the original date of submission of tenders.

- 1. The work is estimated to cost **Rs. 23,48,008/-** This estimate, however, is given merely as a rough guide.
- 2. Agreement shall be drawn with the successful bidders on prescribed (or other Standard Form as mentioned) which is available as a Govt. of India Publication and also available on website. The tender forms and other details can be obtained from the website <a href="https://www.pmml.nic.in">https://www.pmml.nic.in</a> and <a href="https://www.pmml.nic.in">https://www.pmml.nic.in</a> and <a href="https://www.pmml.nic.in">https://www.pmml.nic.in</a> and <a href="https://www.nmml.ewizard.in">https://www.nmml.ewizard.in</a> and financial bids is to be submitted online through e-wizard portal. Bidders shall quote his rates as per various terms and conditions of the said form which will form part of the agreement.
- 3. The time allowed for carrying out the work will be **30 Days** from the date of start as defined in schedule 'F' or from the first date of handing over of the site, whichever is later, in accordance with the phasing, if any, indicated in the tender documents.
- 4. The site for the work shall be made available in parts/Full.
- 5. The bid document consisting of plans, specifications, the schedule of quantities of various types of items to be executed and the set of terms and conditions of the contract to be complied with and other necessary documents except Standard General Conditions of Contract Form can be seen from website <a href="https://www.pmml.nic.in">https://www.pmml.nic.in</a> and <a href="https://www.nmml.ewizard.in">https://www.nmml.ewizard.in</a>.
- 6. After submission of the bid the bidder can re-submit revised bid any number of times but before last time and date of submission of bid as notified.
- 7. While submitting the revised bid, bidder can revise the rate of one or more item(s) any number of times (he need not re-enter rate of all the items) but before last time and date of submission of bid as notified.
- 8. When bids are invited in three stage system and if it is desired to submit revised financial bid then it shall be mandatory to submit revised financial bid. If not submitted, then the bid submitted earlier shall become invalid.
- 9. Earnest Money in the form of insurance Surety Bonds, Account Payee Demand Draft, Fixed Deposit Receipt, Banker's Cheque or Bank Guarantee (for balance amount as prescribed) from any of the commercial Banks drawn in favour of **Director, Prime Ministers Museum and Library**, shall be scanned and uploaded to the e-Tendering website within the period of bid

submission.

A part of earnest money is acceptable in the form of bank guarantee also. In such case, minimum 50% of earnest money or Rs. 20 lacs, whichever is less, shall have to be deposited in shape prescribed above, and balance may be deposited in shape of Bank Guarantee of any Commercial Bank having validity for six months or more from the last date of receipt of bids which is to be scanned and uploaded by the intending bidders.

The earnest money given by all the tenderers except the lowest tenderer shall be refunded immediately after the expiry of stipulated bid validity period or immediately after acceptance of the successful bidder, whichever is earlier. However, in case of two/ three bid system, earnest money deposit of bidders unsuccessful during technical bid evaluation etc. should be returned within 30 days of declaration of result of technical bid evaluation.

Copy of Enlistment Order and certificate of work experience and other documents as specified in the press notice shall be scanned and uploaded to the e-Tendering website within the period of bid submission. However, certified copy of all the scanned and uploaded documents as specified in press notice shall have to be submitted by the lowest bidder only along with physical EMD of the scanned copy of EMD uploaded within a week physically in the office of tender opening authority. Online bid documents submitted by intending bidders shall be opened only of those bidders, whose original EMD deposited and other documents scanned and uploaded are found in order.

9A. The contractors registered prior to 01.04.2015 shall have to deposit tender processing fee at existing rates, or they have option to switch over to the new registration system without tender processing fee any time.

#### The bid submitted shall be opened at 05/12/2025 at 11:00 AM

## 10. The bid submitted shall become invalid and e-Tender processing fee (If applicable) shall not be refunded if:

- (i) The bidder is found ineligible.
- (ii) The bidder does not upload scanned copies of all the documents stipulated in the bid document.
- (iii) If any discrepancy is noticed between the documents as uploaded at the time of submission of bid and hard copies as submitted **physically by the lowest bidder** in the office of bid opening authority.
- (iv) If a tenderer quotes nil rates against each item in item rate tender or does not quote any percentage above/below on the total amount of the tender or any section / sub head in percentage rate tender, the tender shall be treated as invalid and will not be considered as lowest tenderer.
- 11. The contractor whose bid is accepted will be required to furnish performance guarantee at specified percentage of the tendered amount as mentioned in schedule E and within the period specified in Schedule F. This guarantee shall be in the form of insurance Surety Bonds, Account Payee Demand Draft, Fixed Deposit Receipt or Bank Guarantee from any of the Commercial Banks in accordance with the prescribed form. In case the contractor fails to deposit the said performance guarantee within the period as indicated in Schedule 'F', including the extended period if any, the Earnest Money deposited by the contractor shall be forfeited automatically without any notice to the contractor. The earnest money deposited along with bid shall be returned after receiving the aforesaid performance guarantee. The

contractor whose bid is accepted will also be required to furnish either copy of applicable licenses/ registrations or proof of applying for obtaining labour licenses, registration with EPFO, ESIC and BOCW Welfare Board including Provident Fund Code No. if applicable and also ensure the compliance of aforesaid provisions by the sub-contractors, if any engaged by the contractor for the said work within the period specified in Schedule F.

#### 12. The description of the work is as follows:

Annual Repair work and M/o of Library building PMML campus during 2025-26(SH: Repair and replacement of old Rusted C.I pipe line in shaft etc) Teen Murti House, New Delhi..

Intending bidders are advised to inspect and examine the site and its surroundings and satisfy themselves before submitting their bids as to the nature of the ground and sub-soil (so far as is practicable), the form and nature of the site, the means of access to the site, the accommodation they may require and in general shall themselves obtain all necessary information as to risks, contingencies and other circumstances which may influence or affect their bids. A bidder shall be deemed to have full knowledge of the site whether he inspects it or not and no extra charge consequent on any misunderstanding or otherwise shall be allowed. The bidders shall be responsible for arranging and maintaining at his own cost all materials, tools & plants, water, electricity access, facilities for workers and all other services required for executing the work unless otherwise specifically provided for in the contract documents. Submission of a bid by a bidder implies that he has read this notice and all other contract documents and has made himself aware of the scope and specifications of the work to be done and of conditions and rates at which stores, tools and plant, etc. will be issued to him by the Government and local conditions and other factors having a bearing on the execution of the work.

- 13. The competent authority does not bind itself to accept the lowest or any other bid and reserves to itself the authority to reject any or all the bids received without the assignment of any reason. All bids in which any of the prescribed condition is not fulfilled or any condition including that of conditional rebate is put forth by the bidders shall be summarily rejected.
- 14. Canvassing whether directly or indirectly, in connection with bidders is strictly prohibited and the bids submitted by the contractors who resort to canvassing will be liable to rejection.
- 15. The competent authority reserves to himself the right of accepting the whole or any part of the bid and the bidders shall be bound to perform the same at the rate quoted.
- 16. The bid for the works shall remain open for acceptance for a period of Thirty (30) days from the date of opening of bid. If any bidders withdraw his bid before the said period or issue of letter of acceptance, whichever is earlier, or makes any modifications in the terms and conditions of the bid which are not acceptable to the department, then the Government shall, without prejudice to any other right or remedy, be at liberty to forfeit 50% of the said earnest money as aforesaid. Further the bidders shall not be allowed to participate in the retendering process of the work.
- 17. This notice inviting bids shall form a part of the contract document. The successful bidder/contractor, on acceptance of his bid by the Accepting Authority shall within 15 days from the stipulated date of start of the work, sign the contract consisting of:
  - a) The Notice Inviting bid, all the documents including additional conditions, specifications and drawings, if any, forming part of the bid as uploaded at the time of invitation of bid and the rates quoted online at the time of submission of bid and acceptance thereof together with any correspondence leading thereto.

- b) Standard C.P.W.D. Form-7 or other Standard C.P.W.D. Form as applicable.
- 20 Water charges @1% Labour Welfare cess @1%, Income Tax, Surcharge and GST as per applicable Govt. rule shall be deducted from the gross amount of the bill.
- 21. The intending bidders are required to update their profile in CPWD e- tender portal and to upload their bids well in advance of last date of submission of tender. Any issue related to updating profile/uploading tender can be resolved through the concerned Engineer-in-charge. The e- tendering bidders are also advised not to wait to raise any issues till the last date of submission of bid in their own interest.

**Director** 

PMML Teen Murti Campus New Delhi

## Form 'A'

### RECEIPT OF DEPOSITION OF ORIGINAL EMD

	(Receipt No	•••••	)					
	Name of work :-		Annual Repair work and M/o of Library building PMML campus during 2025-26(SH Repair and replacement of old Rusted C.I pipe line in shaft etc) Teen Murti House, New Delhi					
	NIT No.	:-	76-16/2025-26/Admin/Engg/Procurement					
	Estimated Cost	:-	Rs. 23,48,008/-					
	Earnest money deposit	:-	Rs. 70,440/-					
Last date of Submission of Bid:-			05/12/2025 by 5:30 PM					
# 1. N	ame of contractor							
# 2. Fo	orm of EMD							
# 3. A	mount of Earnest Money Depo	osit						
# 4. D	# 4. Date of submission of EMD							
# To b	e filled by EMD receiving in t	he office	e of Director of PMML					

Signature,

Name and Designation of EMD Receiving officer

(PMML) along with Office stamp

#### Form 'F'

# <u>Undertaking on structural stability and soundness of already completed buildings and infrastructure projects.</u>

l/we undertake and confirm that any building / infrastructure constructed by our firm /partnership firm/ company has not suffered any failure, making it unfit for intended use, either due to structural design and defects or due to use of sub-standard materials or execution of sub-standard work, poor workmanship or any other reason during the last 25 (twenty five) years.

l/we, further, undertake that if such information comes to the notice of PMML, then Engineer-in-Charge shall be free to terminate the bid/agreement and to forfeit the entire amount of earnest money deposit, performance guarantee and security deposits.

The decision of Engineer-in-Charge or any higher authority shall be final and binding.

Signature of Signature of bidder or an notary with seal authorized person of the firm

**Note:** Affidavit to be furnished on a 'Non-judicial' stamp paper of Rs. 200/-(scanned copy of the notarized affidavit to be uploaded at the time of submission of bid).

with stamp

### INFORMATION AND INSTRUCTIONS FOR CONTRACTORS FOR e- TENDERING FORMING PART OF NIT AND TO BE POSTED ON WEBSITE

(Applicable for inviting open bids)

The **Director of PMML Teen Murti Campus, New Delhi.** invites online **PERCENTAGE RATE** bids from approved and eligible Contractors of CPWD in appropriate category for the following work(s): -

S. No.	NIT N0.	Name of work & Location	Estimate d cost puts to bid(s)	Earnest money	Stipulated period of completion of work.	Last date of online submission Of bid, copy of receipt of deposition of original EMD and other documents as specified in the bid document.	Date & time of opening of bid
1	2	3	4	5	6	7	8
1	76-16/2025- 26/Admin/Engg/Procurement	Annual Repair work and M/o of Library building PMML campus during 2025- 26(SH Repair and replacement of old Rusted C.I pipe line in shaft etc) Teen Murti House, New Delhi	Rs.23,48,008/	Rs. 70,440	30 Days	upto 05/12/20 25 by 5:30 PM	On 06/12/2025 at 11:00 AM

- 1. The intending bidder must read the terms and conditions of CPWD-6 carefully. He should only submit his bid if he considers himself eligible and he is in possession of all the documents required.
- 2. Information and Instructions for bidders posted on website shall form part of bid document and to be posted on website.
- 3. The bid document consisting of plans, specifications, the schedule of quantities of various types of items to be executed and the set of terms and conditions of the contract to be complied with and other necessary documents can be seen and downloaded from website <a href="https://www.pmml.nic.in">https://www.pmml.nic.in</a> and <a href="https://www.nmml.ewizard.in">https://www.nmml.ewizard.in</a>.
- 4. But the bid can only be submitted after deposition of original EMD either in the office of inviting bids, Account Payee Demand draft or Bankers Cheque or Fixed Deposit Receipts or/ and Bank Guarantee (for balance amount as prescribed) from any of the Commercial Bank towards EMD in favour of **Director**, **Prime Ministers Museum and Library** as mentioned in NIT, receipt for deposition of original EMD to office of **F.A.O Prime Ministers Museum and Library**, **Teen Murti House**, **New Delhi**.
- 5. Those contractors not registered on the website mentioned above, are required to get registered beforehand. If needed they can be imparted training on online bidding process as per details available on the website.

- 6. The intending bidder must have valid digital signature to submit the bid.
- 7. On opening date, the contractor can login and see the bid opening process. After opening of bids, he will receive the competitor bid sheets.
- 8. Contractor can upload documents in the form of **JPG** format and **PDF** format.
- 9. Contractor must ensure to quote rate of each item. The column meant for quoting rate in figures appears in pink colour and the moment rate is entered, it turns sky blue.

In addition to this, while selecting any of the cells a warming appears that if any cell is left blank the same shall be treated as "0". Therefore, if any cell is left blank and no rate is quoted by the bidder, rate of such item shall be treated as "0" (Zero).

However, If a tenderer quotes nil rates against each item in item rate tender or does not quote any percentage above/below on the total amount of the tender or any section / sub head in percentage rate tender, the tender shall be treated as invalid and will not be considered as lowest tenderer.

#### List of Documents to be scanned and uploaded within the period of bid submission: -

1.	Insurance Surety Bonds / Account Payee Demand Draft/ Pay order or Banker's Cheque/ FDR/Bank Guarantee of any Commercial Bank against EMD.
2.	Copy of receipt for deposition of original EMD to F.A.O, Prime Ministers Museum and Library.
3.	Enlistment order of the contractor.
4.	GST Registration Certificate of the State in which the work is to be taken up, if already obtained by the bidder.
	If the bidder has not obtained GST registration as applicable, then he shall scan and upload following undertaking along with bid documents.  "If work is awarded to me, I/we shall obtain GST registration certificate, as applicable, within one month from the date of receipt of award letter or before release of any Payment by CPWD, whichever is earlier, failing which I/we shall be responsible for any delay in payments which will be due towards me/us on account of the work executed and/or for any action taken by CPWD or GST department in this regard".
5.	Undertaking on structural stability and soundness as per prescribed format Form 'F'.
6.	Any other document as specified in the NIT.

(**Note 1: -** The Contract agency participating in the bid shall ensure the uploading of above mandatory documents in eligibility documents/ additional documents portal so that the same can be free viewed & examined before opening the part of their financial bid.)

Director

PMML Teen Murti Campus New Delhi

CORRECTION: NIL, INSERTION: NIL, OVERWRITING: NIL, DELETION: NIL, SR. D/MAN

•

Form-7

# GOVERNMENT OF INDIA PRIME MINISTERS MUSEUM AND LIBRARY PERCENTAGE RATE TENDER & CONTRACT FOR WORK

Tender for the work of :- Annual Repair work and M/o of Library building PMML campus during 2025-26(SH Repair and replacement of old Rusted C.I pipe line in shaft etc) Teen Murti House, New Delhi...

To be uploaded by **05/12/2025** by 05:30 PM

To be opened **06/12/2025** at 11:00 AM online

#### **TENDER**

I/We have read and examined the notice inviting tender, schedule, A, B, C, D, E & F Specifications applicable, Drawings & Designs, General Rules and Directions, Conditions of Contract, clauses of contract, Special conditions, Schedule of Rate & other documents and Rules referred to in the conditions of contract and all other contents in the tender document for the work.

I/We hereby tender for the execution of the work specified for the within the time specified in Schedule 'F' viz., schedule of quantities and in accordance in all respect with the specifications, designs, drawing and instructions in writing referred to in Rule-1 of General Rules and Directions and in Clause 11 of the Conditions of contract and with such materials as are provided for, by, and in respect of accordance with, such conditions so far as applicable.

A copy of earnest money deposit receipt of prescribed amount deposited in the form of, Account Payee Demand Draft, Fixed Deposit Receipt, Banker's Cheque or Bank Guarantee (as prescribed) issued by a Commercial Bank, is scanned and uploaded (strike out as the case may be). If I/We, fail to furnish the prescribed performance guarantee within prescribed period, I/We agree that the said or his successors, in office shall without prejudice to any other right or remedy, be at liberty to forfeit the said earnest money absolutely. Further, if I/We fail to commence work as specified, I/ We agree that or the successors in office shall without prejudice to any other right or remedy available in law, be at liberty to forfeit the said performance guarantee absolutely. The said Performance Guarantee shall be a guarantee to execute all the works referred to in the tender documents upon the terms and conditions contained or referred to those in excess of that limit at the rates to be determined in accordance with the provision contained in Clause 12.2 and 12.3 of the tender form.

Further, I/We agree that in case of forfeiture of Earnest Money or Performance Guarantee as aforesaid, I/We shall be debarred for participation in the re-tendering process of the work.

I/We hereby declare that I/We shall treat the tender documents drawings and other records connected with the work as secret/confidential documents and shall not communicate information/derived there from to any person other than a person to whom I/We am/are authorized to communicate the same or use the information in any manner prejudicial to the safety of the State.

Dated: #	
Witness:#	Signature of Contractor #
Address: #	Postal Address #
Occupation: #	
<b>#</b> To be filled by the contractor	
ACCEPI	<u> FANCE</u>
The above tender (as modified by you as provid accepted by me for and on behalf of the Director	
*	
(Rupees	).
The letters referred to below shall form part of t (a)	his contract agreement: -
(b)	
(c)	
	Signature
Dated:	
	Designation

#### PROFORMA OF SCHEDULES

#### PROFORMA OF SCHEDULES

**SCHEDULE 'A'** 

Schedule of quantities: -Page No. 38 to 50

**SCHEDULE 'D'** 

General Conditions	As per page–27 to 30
Special Condition	As per page–31 to 33
Condition for Cement & Steel	As per page– 34 to 35

#### SCHEDULE 'E'

1.	Reference to	<b>General Condition of Contract for CPWD</b>
	General Conditions	works – 2023 (Maintenance work)
	of contract	modified and corrected up to previous day
		of the last date of submission of tender.

Name of Work: Annual Repair work and M/o of Library building

PMML campus during 2025-26(SH Repair and replacement of old Rusted C.I pipe line in shaft

etc) Teen Murti House, New Delhi..

Estimated Cost of Work: Rs. 23,48,008/-

Earnest money: Rs. 70,440/-

(i) Performance Guarantee: 5% of tendered value.

#### **SCHEDULE 'F'**

#### **General Rules & Directions:**

Officer inviting tender : **Director of PMML Teen Murti** 

Campus, New Delhi

**Definitions:** 

2(v) Engineer-in-Charge : Sh. A. K. Tyagi, Consultant

2(viii) Accepting Authority : Director of PMML Teen Murti

Campus, New Delhi.

2(x) Percentage on cost of materials and : 15%

Labour to cover all overheads and

profit

2(xi) Standard schedule of Rates : **DSR 2023 with upto date** 

**Correction slips & Market** 

Rate.

2(xii) Department : **PMML Department** 

9(ii) Standard CPWD contract form : **CPWD form – 7, General** 

Conditions of Contract
Maintenance work 2023 as
modified & corrected up to
previous day of last date of
submission of tender.

#### Clause-1

i) Time allowed for submission of :
Performance Guarantee, Programme
Chart (Time and Progress) and
Applicable labour license, registration
With EPFO, ESIC and BOCW Welfare
Board or proof of applying

Thereof from the date of issue of letter of acceptance,

ii) Maximum allowable extension
Late fee@ 0.1% per day of
Performance guarantee amount
beyond the period provided in (i)
above

3 Days

:

7 Days

#### Clause 2.

Authority for fixing compensation :

under Clause 2. **Director of** 

PMML Teen Murti Campus, New Delhi

#### Clause 2A

Whether Clause 2A shall be : No

applicable

#### Milestone(s) as per table given below :- : Not Applicable

#### Table of Mile Stone (s)

Not Applicable								
			milestone					
No.	(Physical)	(from date of start)	case of non-achievement of					
Sl.	Description of Mile Stone	Time allowed in days	Amount to be withheld in					

Time allowed for execution of work : 30 Days

#### **Authority to Decide:**

1. To convey the decision of **Director**,

shifting of milestone and PMML Teen Murti Campus,

extension of time New Delhi.

2. Re-scheduling of mile stones

extension of time

: Director , and PMML Teen Murti, Campus New Delhi,

3. Shifting of date of start in

case of delay in handing over of

: Director, PMML Teen Murti campus New Delhi.

#### Clause 5

Clause applicable – (5 or 5A) : Clause-5

Number of days from the date of issue of acceptance for reckoning

date of start : 10 days

Clause 6 : Computerized

Measurement book (CMB)/ Electronic Measurement book

(EMB)

Mode of measurement : **EMB** 

#### Clause 7

Gross work to be done together : **N.A** 

With net payment/adjustment

of advances for material collected

If any, since the last such payment for Being eligible to interim payment

Clause 7 (A) Whether clause 7A shall be : No applicable

#### Clause 10 A

List of testing equipment to be : As per site requirement

provided by the contractor at site lab.

Clause 10 B (ii)

Whether clause 10 B (ii) : No

shall be applicable

Clause 10 C : Not applicable

Component of labour expressed as Percentage of value of work.l

25%

Clause 10 CA : Not Applicable

Clause 10 CC : Not Applicable

Clause 11

Specification to be followed for this work : The work shall be carried out as per

CPWD Specification 2019 Vol-I & II with upto date correction slips & as per direction of Engineer-in Charge

Clause 12

Type of Work:- Maintenance work

The completion cost for maintenance work shall in no case not exceed 1.50 times of the contract amount.

Authority to decide deviation upto : Director, PMML, Teen Murti House, New Delhi.

1.25 times of tendered amount

Authority to decide deviation beyond :Director, PMML, Teen Murti House, New Delhi.

1.25 times & up to 1.50 times

of tendered amount

12.2 & 12.3 Deviation limit beyond which : NO LIMIT

clause 12.2 & 12.3 shall apply (All deviated quantities shall be

for Building work Paid on agreement rates)

12.5(i) Deviation limit beyond which : -----DO----

clause 12.2 & 12.3 shall apply

for foundation works (except items mentioned in earth work

Sub-Head in DSR and related items)

(ii) Deviation limit for items in earth : ----DO----

Work subhead of DSR or related items

Clause 16	Competent Authority for Deciding redu	ced rates: Director, PMML, TMH, ND.
Clause 18	List of mandatory machinery, tools & plants to be deployed by the contractor at site.	As per requirement at site and direction of Engineer—in-Charge.

#### Clause 19

Clause 19C Authority to decide penalty for each default-----
Clause 19D Authority to decide penalty for each default-----
Clause 19G Authority to decide penalty for each default-----
Clause 19K Authority to decide penalty for each default------

#### Clause 25

(i) Conciliator: Director, PMML, Teen Murti House, ND

(ii) (ii) Arbitrator Appointing Authority: -do-(iii) (iii) Place of Arbitration: -do-

#### Clause 32

Cla	Clause 32								
"Re	quirement of Te	chnical Repre	sentative (s) and	<b>Recovery Rate</b>	es"				
SI. No.	Minimum qualification of Technical Representative	Discipline for (Major + Minor component)	Designation (Principal Technical /Technical Representative	Minimum Experience (years)	Number	Rate at which recovery shall be made from the contractor in the event of not fulfilling provision of clause 32(i) (Rs per month per person)  Figures words			
1	Graduate Engineer or Diploma Engineer	Civil (1)	Project manager cum planning / quality /site billing Engineer	2 or 5 respectively	1	30,000/-	Rupees Thirty Thousand only		

#### Note:

- a. Assistant Engineers retired from Government services that are holding Diploma will be treated at par with Graduate Engineer.
- b. Diploma holder with minimum 10 years' relevant experience with a reputed construction co. can be treated at par with Graduate Engineers for the purpose of such deployment subject to the condition that such diploma holders should not exceed 50% of requirement of degree engineer

#### Clause 38

I) (a) Schedule/statement for determining theoretical quantity of cement & bitumen : Delhi Schedule of Rates 2023

II) Variations permissible on theoretical quantities:

(a) Cement

For works with estimated cost put to tender

not more than Rs. 25 lakh. : 3% plus/minus.

For works with estimated cost put to tender

more than Rs. 25 lakh. : 2% plus/minus.

(b) Bitumen for all works : 2.5% plus only and nil on

minus side.

(c) Steel Reinforcement and structural steel sections for each diameter, section and category: 2% plus/minus

(d) All other materials. : NIL

**Director** 

PMML Teen Murti Campus

New Delhi.

#### 1. SCOPE OF WORK

1.1 Repair work of Store near Annexe Building, PMML Teen Murti House, New Delhi, during 2025-26.

#### 2.0 General specifications

2.1 The common & general specifications for accommodations are mentioned below for guidance only.

**Structure** - as per schedule

**Masonry** - -do-

**External plaster** - -do-

External Finishing - -do-

**Internal Finishing** - -do-

Windows - -do-

**Flooring** - a. Rooms – -do-

b. Washrooms & Kitchen - -do-

c. Verandah or Porch – -do-.

2.2 **Boundary wall** - -do-

**Height** - do-

**Finishing** - -do-

#### **ANNEXURE-I**

## GUARANTEE TO BE EXECUTED BY CONTRACTORS FOR REMOVAL OF DEFECTS AFTER COMPLETION IN RESPECT OF WATER PROOFING WORKS.

	The	Agreer etween	nent	made	this			son	•	of _	of	two	thousa	ınd	and
of		AWCCII		(herein	after ca	alled	the Gua			ne one	_	and the	Directo	or, PN	ИMI
(herei	nafter c	alled the	Gove	ernment	of the o	other	part).				•				
	nment	of the of	her pa	and a	made beby the	etwe Con	een the tractor, <i>i</i>	GUAl inter a	RAN <i>lia</i> , u	TOR inderto	OF T	HE ON	NE part	and	the
structi treatm	ıres wi	WHER					-	_		_					
	the str	THE Guctures of to be re-	omple	etely leal	k-proof	and	the mini	mum l	life o	f such	water	proofin	g treatn	nent	
structi		ding thateets or n									age ca	used b	y earth	quak	e or
a		se of roo ewood aı									_			chop	ping
b		ation sha							•	-			f or con	struc	ction
c	) The d	lecision of	of the	Enginee	r-in-cha	arge	with rega	ard to	caus	e of lea	kage	shall be	final.		
cost a notice be go	being nd shall from to done l	ng this portion of the comment of the Engire of the Donard of the Donard of the Donard of the Engine	nder the contract of the contr	the build ne work f n-charge ment by	ing wa or such calling some o	ter protection terms of the ter	roof to the ification in him to Contrac	he sat withi rectif tor at	isfact n sev y the the (	tion of en day defect GUAR	the E s fror s faili ANT(	ngineer n the da ng whic DR'S co	:-in-cha te of iss ch the w ost and	rge a sue o vork risk.	t his f the shall The
othery perfor and /o	ntor wi vise wh mance	if the Guill indemich may and obsence to the control of the contro	nnify to be increased	the Princ neurred be se of this	cipal an by him supple	d his by re ment	s success eason of ary agree	sors a any d ement	gains defau . As t	st all loalst the action to th	oss, da part o moun	amage, f the G t of loss	cost, ex UARAl s and / o	xpens NTO or dan	se or R in nage
IN Obligo behalf		NESS Director	WHI	EREOF  ML on th	thes and l	se by mont	present	ar firs	have	beove wri	en tten			oy or an	the d on
		d and de							or acc	, v	ttom.				
Ū				•	•	•		01 —							
<b>-</b> ·	S	igned fo	r and	on behal	f of the	Dire	ector, PN	/ML t	оу _						
In the	presen						,		<i>-</i>						_
1.							2.					_			

# ANNEXURE-II GUARANTEE TO BE EXECUTED BY CONTRACTORS FOR REMOVAL OF DEFECTS AFTER COMPLETION IN RESPECT OF ANTI-TERMITE TREATMENT WORKS.

The Agre	eement made this		aay of				thousan	d and
	etween _			son	of_			
of			the Guaran		the one	part) and	the D	irector
,PMML(nereinar	ter called the Govern	iment of the	e otner part)	•				
dated Government of the	AS THIS agreement and more other part, wherebaid contract recited	ade between the Control	en the GUA actor, <i>inter</i>	ARANTO alia, und	OR OF T	THE ONE	part an	d the
structures in the	said contract recried	completely	termite proc	<i>7</i> 1.				
	HEREAS THE GUA main termite proof for							
render the struct years to be recked During the defect being four cost and shall con notice from the E be got done by the decision of the E	HE GUARANTOR ures completely terroned from the date and is period of guaranted render the building mence the work for Engineer-in-charge control by songineer-in-charge as	tee, the guage termite profession of the cost, and the cos	and the min ntenance per rantor shall coof to the sa- fication with him to recti Contractor a payable by	imum liftiod pressonates goatisfaction seven fy the det the GU the Guar	e of such cribed in bod all de n of the l days fro- fects fail ARANT rantor sha	n treatment the contract efects and in Engineer-in the date ing which to OR'S cost all be final a	shall be t. n case of a-charge of issue the work and risk and bind	of any at his of the c shall c. The ling.
the Guarantor wi otherwise which performance and	ne Guarantor fails to Il indemnify the Prir may be incurred by observance of this so red by the Governme	ncipal and he him by resupplementa	is successor ason of any ry agreemen	s against default at. As to t	all loss, the part of he amour	damage, co of the GUA nt of loss an	st, expe ARANTO ad / or da	nse or OR in amage
IN WITN Obligor_ behalf of the Dire	ESS WHEREOF ector, PMML on the	_and by	presents and year fir	have	been written.	executed	l by and for a	the and on
Signed, sealed an	nd delivered by Oblig	gor in the pr	esence of –					
_		_						
	n behalf of the Direc		by					
In the presence o		, - 1.11.11	- J			_		
•	•		2					

#### GENERAL TERMS AND CONDITIONS

- 1. The contractors are advised to get acquainted with the proposed work and its site and also study the Architectural Drawings, specifications and special conditions carefully before tendering. No claim of any sort shall be entertained on account of any site conditions and ignorance of specifications and special conditions
- 2. The work shall be carried out as per CPWD specifications 2023 (Vol. I & II) with up to date correction slips. For items which are not covered under CPWD specifications, the special conditions / BIS specifications shall apply. In this regard the decision of Engineer-in-Charge shall be final.
- 3. All materials, T & P, consumable and contingent articles required for the work shall be arranged by the contractor. Materials used shall be in preference as per the nomenclature of the item / as per approved list / CPWD Specifications and as per directions of Engineer-in-Charge. Replaced materials used shall have same or richer specifications to the original materials and compatible to the work. If any of the accessories available in the market is not ISI marked then decision of engineer in charge is final and will be binding to the contractor.
- 4. All the malba /rubbish /silt /waste / garden waste etc. generated due to any operation / execution of the work shall be brought down through the stair case and shall not be thrown to the ground directly from the upper floors etc. Malba rubbish generated due to any operation from Bungalows/ quarters / premises and its open spaces whatsoever shall be disposed off by the Contractor to the specified dumping point on daily basis else a recovery of Rs. 100/- per Bungalows/ quarters / premises per day shall be made from contractor. The dumping point should be properly barricaded at all the time and should not give ugly look. This malba / rubbish shall further be disposed to the authorized municipal dhalao / dumping ground as and when the quantity becomes 4.5 cum or one truck and as per direction of Engineer-in-charge. The Malba/rubbish kept inside the dumping point should be covered with sheet or any other suitable material to avoid dust pollution. In case of malba / rubbish does not got removed from dumping point, a recovery of Rs. 1000/- (rupees One thousand) per day shall be made from the contractor after issuing notice in writing by the Engineer in charge of work. If the malba is not removed within three days of notice, the same shall be got removed by the department at the risk and cost of the Contractor and the amount shall be recovered from the bill of Contractor. This is in addition to the recovery of Rs. 1000/- per day for delay in removal of malba
- 5. The contractor or his representative shall be available at site on every visit of officer-in-charge as well as visit of senior officers.
- 6. Chases, holes & drilling works etc. shall be done by using power operated tools.
- 7. The contractor shall have to carry out the work other than day to day maintenance according to program given by the Engineer-in-charge. The contractor shall not carry out any work in any building without permission of Engineer-in-charge or his authorized representatives. The contractor shall have to adhere to this program failing which he shall be wholly responsible for any inconvenience caused to the occupants. No claim for idle labour on any account shall be entertained. The contractor shall depute his representative daily to the site of work. His name and Signature shall be attested by the contractor for record in the department.
- 8. The site for the collection and stacking of the material shall be got approved from the Engineer-in-charge.
- 9. The sample of all the items shall have to be got approved by the contractor from the Engineer-in-charge before the supply commences and shall be without prejudiced to the right of the Engineer-in-Charge to get random samples tested out of the actual lot received.

- 10. The Engineer-in-Charge will be at liberty to take respective sample(s) of each item of Schedule of Quantity in any approved laboratory as decided by him. The sample for testing will be provided by the contractor. All expenditure required to be incurred for taking sample, conveyance, packing and testing charges etc. will be borne by the contractor himself. In case any sample particular lot fails in testing, the contractor will be bound to replace the entire lot with fresh material of prescribed specification and the rejected lot will be returned to the contractor only after fresh lot is supplied.
- 11. Rejected materials will have to be removed by the contractor at his own cost immediately of the instructions of doing so.
- 12. In case of any dispute regarding rejection of quality of materials, the decision of the Engineer-in-Charge will be final and binding upon the contractor.
- 13. Other agencies may also be simultaneously executing some other work entrusted to them by the Engineer-in-charge and the Contractor shall offer necessary co-operation wherever required to these agencies so as not to interfere with or hinder the progress or completion of the work being performed by other Contractor (s). He shall as far as possibly arrange his work and shall place and dispose off the materials being used or removed, so as not to interfere with the operations of other Contractors, or he shall arrange his work with that of the others in an acceptable and coordinated manner and shall perform it in proper sequence to the complete satisfaction of Engineer-in-charge.
- 14. Contractor shall ensure the cleanness and watch & ward of the premises / vacant bungalows / quarter / garages etc. till further occupation of the same.
- 15. All taxes applicable at prevalent rates shall have to be paid by the contractor himself and the rates quoted by him shall include these taxes and nothing extra on this account shall be payable.
- 16. The rates for different items of work shall apply for all heights and depths, leads and lifts unless otherwise specified in the agreement or specifications applicable to the agreement.
- 17. Any damage done by the contractor to any existing work during the course of execution of the work shall be made good by him at his own cost.
- 18. Articles manufactured by the reputed firms and approved by Engineer-in-Charge shall only be used. Only articles classified, as 'first quality' by the manufacturer shall be used unless otherwise specified. In case articles bearing ISI certification are not available in the market, quality of samples brought by the contractor shall be judged by standards laid down in the relevant CPWD specifications. For the items not covered by CPWD specifications relevant BIS standards shall apply. The sample of materials to be brought to site for use in work shall be got approved from the Engineer-in-Charge before actual execution of work.
- 19. The contractor shall submit a detailed program of work within 15 days of the date of award of work. The Engineer-in-Charge can modify the program and the contractor shall have to work accordingly.
- 20. The quantities of any item shall not be exceeded beyond the agreement quantities without prior permission of Engineer-in-Charge.
- 21. Statutory recoveries such as on account of GST, Income tax, Surcharge, Construction Worker's Welfare Cess etc. as applicable from time to time shall be made from the gross amount of Running A/c Bill and Final Bill of the contractor.
- 22. The contractor shall make his own arrangements for obtaining electric connection, if required and make necessary payments directly to the department concerned. In the absence of electric connection or failure of power supply, the Contractor shall make his own arrangement of silent type generators as per NGT Guidelines.
- 23. The contractor shall make his own arrangement for getting the permission for entry of trucks carrying materials for the site from the traffic police.
- 24. No payment shall be made to the contractor for any damage caused by rain, snow fall, floods or any other natural causes whatsoever during the execution of work. The damage caused to work shall have to be made good by the contractor at his own cost and no claim on this account shall be entertained.

- 25. The contractor shall take all precautions to avoid accidents by exhibiting necessary caution boards / signages, warning boards, red flags, red lights and providing necessary barriers / barricading of the construction area and all other measures required from time to time, **nothing extra shall be paid to agency on this account.** He shall be responsible for all damages and accidents caused due to negligence on his part. No hindrance shall be caused to traffic during the execution of the work by storing materials on the road.
- 26. The contractor shall be fully responsible for the safe custody of the material issued or brought by him to site for doing the work.
- 27. If due to exigency of work, the work is required to be carried out in more than one shift or during night then Contractor will be bound to execute the work accordingly and arrange the T & P and labour etc. No extra claim on this account shall be entertained.
- 28. The rate for all items of work shall, unless otherwise clearly specified, include cost of all labour, material and other inputs involved in the execution of the items.
- 29. In case of any discrepancy found in NIT / tender documents, the order of preference may be read as the following.
  - a) Description of Schedule of quantities
  - b) Particular Specifications, Additional Conditions and Special Conditions, if any.
  - c) Architectural Drawings
  - d) CPWD Specifications with up to date correction slips.
  - e) Indian Standard Specifications / BIS
  - f) Sound engineering practice.
- 30. Any reference made to any Indian Standard Specifications in these documents, shall imply to the latest version of that standard, including such revisions / amendments as issued by the Bureau of Indian Standards up to last date of receipt of tenders. The contractor shall keep at his own cost all such publications of relevant Indian Standards applicable to the work at site.
- 31. The contractor will not have any claim in case of any delay by the Engineer-in-Charge in removal of trees or shifting, removing of telegraph, telephone or electric lines (overhead or underground), water and sewer lines and other structure etc., if any which may come in the way of the work. However, suitable extension of time can be granted to cover such delay.
- 32. The contractor shall clean the site thoroughly of scaffolding materials, rubbish, equipment left out of his work and dress the site around the building to the complete satisfaction of the Engineer-in-charge before the work is treated as completed.
- 33. No residential accommodation shall be provided to any of the staff engaged by the contractor. The contractor shall also not be allowed to erect any permanent / temporary set up for his staff in the premises.
- 34. Contractor has to provide drinking water facility in each enquiry office by providing necessary filter (RO) with and his staff. Watch & Ward of Enquiry office shall be the responsibility of the contractor.
- 35. The contractor shall comply with proper and legal orders and directions of the local or public authority or Municipality and abide by their rules and regulations and pay all fees and charges which he may be liable.
- 36. The Contractor shall give due notices to Municipality, Police and/ or other authorities that may be required under the law/ rules under force and obtain all requisite licenses for temporary obstructions/ enclosures and pay all charges which may be liveable on account of his execution of the work under the agreement. Nothing extra shall be payable on this account.
- 37. The work shall be carried out in a manner complying in all respects with the requirements of relevant bye laws of the local bodies, labour laws, minimum wages act, workmen compensation act and other statutory laws enacted by Central Govt. as well as State Govt.

- 38. Any damage caused due to negligence of contractor during the routine maintenance shall be of firm's responsibility. The firm has to make good the same at his own risk and cost.
- 39. Site is located in sensitive and high security & VVIP area, where movement and routes are restricted. The Contractor shall have to apply for passes well in advance for carrying out the work. No claim whatsoever shall be entertained for any loss on this account. Some restrictions may be imposed by the Security staff/ Delhi police on the working and for movement of labour, materials etc.
- 40. The movement of trucks and vehicles shall be regulated in accordance with rules and regulations as approved by competent authority.
- 41. The Contractor shall be bound to follow all such restrictions / instructions and nothing extra shall be payable on this account.
- 42. The Contractor is required to prepare and install appropriate number of Display Boards at suitable locations in the colony / office and also at the Service Centre, to apprise the Residents about the details of Engineer-in-charge etc.
- 43. The Contractor shall not stack building material / malba on NDMC land or road or on the land owned by any other authority and in case of failure to do so, he shall face penal action as per the rules, regulation and bye-laws of the said body or authority. The Engineer-in-Charge shall be at liberty to recover the amount due but not paid to the concerned authorities on account of the above from any amount due to the Contractor including amount of the security deposit or retention money in respect of this Contractor or any other Contract.
- 44. The contractor or his representative is bound to sign the site order book as and when required by the Engineer-in-Charge and to comply with the remarks therein.
- 45. The contractor shall take all necessary precautions to prevent any nuisance or inconvenience to the owners, tenants of adjacent properties and to the public in general and to prevent any damage to such properties and any pollution of smoke, streams and waterways. He shall make good at his cost and to the satisfaction of the Engineer-in-Charge, any damage to roads, paths, cross drainage works or public or private property whatsoever caused by the execution of the work or by traffic brought thereon by the contractor. Utmost care shall be taken to keep the noise level to the barest minimum so that no disturbance as far as possible is caused to the occupants / users of adjoining buildings.
- 46. The agency has to ensure the safety and protection of all the existing fittings, floorings, fixtures and all other building parts during execution of work, **nothing extra shall be paid to agency on this account.**
- 47. Agency has to submit measurement of work executed during each month, at least once in a month, failing which a recovery of **Rupees Fifty Thousand per month** shall be made from the next Running account / final bill.

#### 48. **Pollution Control Guidelines**

- The guidelines regarding preventive measures for Air Pollution from demolition & construction activities issued by Delhi Pollution Control Committee vide no. DPCC/EIA/Res-001 to 172/NGT-21/2015/225-408 dated 17.04.2015 and any other guide lines issued till date or during the execution of work, in compliance of Hon'ble National Green Tribunal directions, are applicable to the contractor. All appropriate protective measures as per NGT & DPCC guidelines / directions shall be taken by the contractor and nothing extra shall be payable on this account.
- 49. The contractor shall have to work in pandemic / epidemic conditions such as COVID 19 for which he has to make safety arrangement / measures for the workers / staff and for the premises meant for them, as per guidelines issued by Government and directions issued by Engineer-in-charge from time to time and nothing extra shall be paid on this account.

#### SPECIAL CONDITIONS

- 1. EMD in the name of Director, PMML.
- 2. One work order of 80 % of project value (23,48,008/-) that is around 18.79 Lakhs and two works order of 60 % of the project value (23,48,008/-) that is around is 14.10 Lakhs.
- 3. Bill along with measurement to be submitted by the agency in complete shape.
- 4. In any case, final decision of Director will be binding to all.
- 5. Time for the completion is 30 Days.
- 6. Full quantity or quantity as decided by Engineer-in- Charge of the materials such as paint, Acrylic emulsion paint, Acrylic distemper or any other material required as per schedule of quantity etc. shall be deposited at the office of PMML within 07 days of start of work.
- 7. The contractor shall have to get approved the brands / shades of Acrylic Distemper, Synthetic Enamel Paint, Acrylic Emulsion Paint, Exterior Paint or any other material required as per schedule of quantity etc. from the Engineer-in-Charge within 5 days of start of work and also shall be got checked by the Engineer-in-charge or his authorized representative on receipt of it at site before execution of same.
- 8. The materials required for day's work shall be issued to contractor or his authorized representative daily by the Engineer -in-charge of the work. Any balance of the material left at end of the days of work and the empty containers shall be returned to Engineer -in-charge. The day to day issue account of the materials shall be maintained by the Junior Engineer-in-Charge and shall be signed daily by the Contractor or his authorized agent in token of receipt of the materials failing which no payment of bill shall be made to the Contractor. The empty containers shall not be removed from the site of work without written orders of the Engineer-in-charge.
- 9. Before the commencement of work, the contractor shall prepare one sample as instructed by the Engineer-in-charge. After the sample is approved by the Engineer-in-Charge, the Contractor shall be allowed to commence the work and the quality of work shall confirm to the approved sample.
- 10. In case the Bungalows / quarters are not made available to the Contractor according to the programme, the Contractor shall not be entitled for any claim for idle labour or any other claim on any account what-so-ever.
- 11. No payment will be made to the Contractor for damage caused by rains during the execution of the works and no claim on this account will be entertained.
- 12. Scrapping shall be shown to the Engineer-in-charge and got approved and test checked by him prior to painting or other finishing work.
- 13. To avoid disputes later on, contractor is advised to get the measurement recorded within a week's time and shall submit his bills as per relevant clauses of contract. Any dispute regarding measurement including work done shall be judged within a week's time failing which measurement, certified and recorded, shall be entertained.
- 14. All doors, windows, floors, furniture, electrical fittings and other articles shall be protected from dust, splashes & damage Splashes & droppings from white washing, colour washing, distempering painting etc. on walls, floors, doors and window, down take pipes / furniture shall be removed by the Contractor at his own cost and the surface cleaned simultaneously after the completion of the day's work is done, without waiting for the actual completion of the other items of work of the contract.
- 15. The Contractor shall comply with the provisions of 'Construction and Demolition Waste Management Rules, 2016' as notified by the Ministry of Environment and Forest vide notification dated 29.03.2016 (available at web address <a href="www.moef.gov.in">www.moef.gov.in</a>).
- 16. For some of the specific nature of work such as anti-termite treatment and waterproofing work the specialized agencies to be associated by the contractors. The associated specialized agencies / specialized firm executing the work shall give a specific guarantee that they are responsible for removal of any defects cropping up in these works executed by them during the guarantee period.

- a) The form of the guarantee to be executed by the contractors is given as per annexure attached.
- b) 10% of the amount pertaining to anti-termite treatment and waterproofing work as security deducted from the bills of the contractors will be refunded after expiry of guarantee period in accordance with the terms of the contract in this behalf.
- 17. During execution of work, water supply, installations / fittings & sanitary, installation / fittings, will be dismantled / demolished for which nothing extra shall be paid except the items already exist in the schedule of quantities (civil) attached.
- 18. Any cement slurry added over base surface (or) for continuation of concreting for better bond is deemed to have been included in the items and nothing extra shall be paid on this account.
- 19. If in the description / nomenclature of item the thickness of board / ply is mentioned 18mm thick and manufacturer does not provide / manufacture 18mm thick board / ply then 19mm thick board / ply can be used there, for that nothing extra shall be paid on this account, vice versa.
- 20. Agency should take extra precaution for protection of existing floor, wall, fittings, fixtures etc. Nothing extra shall be paid on this account.
- 21. The dismantled material received from the work shall be the property of contractor for which the credit shall be paid on following rates –

S. No.	Items / Materials	Rate (in Rs.)
(a)	Cast Iron / Steel Scrap	27.30 per kg.
(b)	CP Fittings	560.75 per kg.
(c)	Aluminium Sections, grills, sheets etc.	112.55 per kg.
(d)	Wooden doors & windows	
(i)	Of area upto 3 sqmt.	1000/- each
(ii)	Of area beyond 3 sqmt.	1500/- each
(e)	Old Bricks	2.30 each

#### **CONDITIONS FOR CEMENT & STEEL**

#### 1. Cement

- The contractor shall procure 43 grade (conforming to IS 8112) Ordinary Portland cement/PPC as required in the work, from reputed manufacturers of cement, having a production capacity of one million tonnes per annum or more, such as ACC, JK Cement, Ultratech, Shree Cement, etc., i.e. agencies approved by Ministry of Industry, Govt. of India, and holding license to use ISI certification mark for their product. The tenderers may also submit a list of names of cement manufactures which they propose to use in the work. The Engineer-in-charge reserves right to accept or reject name(s) of cement manufacture(s) which the tenderer proposes to use in the work. No change in the tendered rates will be accepted if the Engineer-in-charge does not accept the list of cement manufacturers, given by the tenderer, fully or partially. Supply of cement shall be taken in 50 kg bags bearing manufacturer's name and ISI marking except for concrete from RMC producer where bulk cement can be procured. Samples of cement arranged by the contractor shall be taken by the Engineer in Charge and got tested in accordance with provisions of relevant BIS Codes. In case test results indicate that the cement arranged by the contractor does not conform to the relevant BIS Codes, the same shall stand rejected and shall be removed from the site by the contractor at his own cost within a week's time of written order from the Engineer in Charge to do so. Only the cement with satisfactory test results shall be allowed to be used in the work.
- 1.2 The quantity of cement shall be brought at site as decided by the Engineer in Charge.
- 1.3 Double lock provision shall be made to the door of the cement store. The key of one lock shall remain with the Engineer in Charge or his authorized representative and the key of the other lock shall remain with the contractor. The contractor shall be responsible for the watch and ward and safety of the cement godown.
- 1.4 The contractor shall supply free of charge the cement required for testing and shall also bear the packing, sealing, transportation & other incidental charges. The testing charges of approved laboratory shall be borne by the contractor.
- 1.5 The day to day actual issue/receipt and consumption of cement on work shall be regulated and proper accounts maintained in cement register which shall be issued by Engineer-in-charge.
- 1.6 Cement brought to site and cement remaining unused after completion of work shall not be removed from site without written permission of the Engineer in Charge.
- 1.7 In the event of it being discovered that after the completion of the work the quantity of cement used is less than the quantity ascertained after allowing variation on the minus side as per clause 38, the cost of quantity of cement not so used shall be recovered from the contractor, at the rate of **Rs. 5500/- (Rupees Five Thousand Five hundred only) per metric ton**. This recovery will be in addition to any other recovery otherwise required to be done by the Engineer-in-Charge.

#### 2. Steel for Reinforcement:

- 1.1 The contractor shall procure steel reinforcement TMT bars of grade Fe-500-D confirming to IS code (latest edition) from main producers as approved by the Ministry of Steel and secondary producers of re-rollers having valid BIS licence for TMT bars conforming to relevant BIS code, procurement shall be made from main producers and secondary producers having valid BIS licence. The name of secondary producer however will have to be got approved by engineer-in-charge before procurement. The contractor shall have to obtain and furnish test certificates to the Engineer in Charge in respect of all supplies of steel brought by him to the site of work. Samples shall also be taken and got tested by the Engineer in Charge as per the provisions in this regard in relevant BIS Codes. In case the test results indicate that the steel arranged by the contractor does not conform to BIS Codes, the same shall stand rejected and shall be removed from the site of work by the contractor at his cost within a week's time from written orders from the Engineer in Charge to do so.
- 1.2 The quantity of steel shall be brought at site as decided by the Engineer in Charge.

- 1.3 The steel reinforcement shall be stored by the contractor at site of work in such a way as to prevent distortion and corrosion and nothing extra shall be paid on this account. Bars of different sizes and lengths shall be stored separately to facilitate easy counting and checking. The cement slurry to be applied to prevent corrosion. The nothing extra shall payable on this account.
- 1.4 For checking nominal mass, tensile strength, bend test, re-bend test etc. specimen of sufficient length shall be cut from each size of the bar section at random at frequency not less than that specified below: -

Size of Bar	For Consignment below 100 tonnes	For Consignment over 100 tonnes
Under 10 mm dia	one sample for each 25 tonnes	one sample for each 40 MT
	or part thereof	or part thereof
10 mm to 16 mm	one sample for each 35 tonnes	one sample for each 40MT
	or part thereof	or part thereof
Over 16 mm dia	one sample for each 45 tonnes	one sample for each 50 MT
	or part thereof.	Or part thereof

- 1.5 The contractor shall supply free of charge the steel reinforcing bars required for testing and shall also bear the packing, sealing, transportation & other incidental charges. The testing charges of approved laboratory shall be borne by the contractor.
- 1.6 The actual issue and consumption of steel on work shall be regulated and proper accounts maintained. The theoretical consumption of steel shall be worked out as per procedure prescribed in clause 38 of the contract and shall be governed by conditions laid therein.
- 1.7 Steel brought to site and steel remaining unused shall not be removed from site without the written permission of the Engineer in Charge.
- 1.8 The contractor shall take all precautions to avoid accidents by exhibiting caution boards day and night. The contractor shall be responsible for all damages and accident due to negligence on his part.
- 1.9 The contractor shall arrange steel reinforcement bars as cut and bend bars from approved workshop/suppliers. In case of non-availability of the same on justified reasons, the same can be manufactured at site, however no extra payment whatsoever shall be made for same.

#### **Minimum Quality Assurance Plan**

#### 1. Maintenance of Register of Tests

- (i) All the registers of tests to be carried out at Construction Sites or in outside laboratories are maintained by the contractor, which are issued to the contractor by Engineer-in-Charge.
- (ii) All Samples of materials including Cement Concrete Cubes are taken jointly with Contractor by Engineer-in-charge as per percentage stipulated in the NIT or as prescribed in the CPWD Works Manual. All the necessary assistance is to be provided by the contractor. Cost of sample of materials including testing charges is to be borne by the contractor and he/she is responsible for safe custody of samples to be tested at site.
- (iii) All the test in field lab setup at Construction Site are carried out by the Engineering Staff deployed by the contractor preferably. The percentages of tests to be witnessed by the field officers are to be decided by the NIT approving authority and stipulated in the NIT keeping in view the nature of work and should form part of QA Plan. In case, no such provision is made in NIT, provisions of CPWD Works Manual shall be applicable.
- (iv) All the entries in the registers are made by the designated Engineering Staff of the contractor and same is regularly reviewed by the field officers as well as the Engineer-in-Charge. Contractor is responsible for safe custody of all the test registers.
- (v) Contractor shall be responsible for safe custody of all the test registers.

Submission of copy of all Test Registers, Material at Site (MAS) Register along with each alternate Running Account Bill and Final Bill shall be mandatory. These registers should be duly checked by Engineer-in-charge and receipts of registers should also be acknowledged by Accounts Officer by signing the copies and register to confirm receipt in Division office.

#### 2. Maintenance of Material at Site (MAS) Register-

- a) All MAS Registers including Cement and Steel Registers are maintained by Contractor which are issued to the contractor by Engineer-in-Charge.
- b) Each entry of receipt of material at site is 100% test checked by Engineer-in-charge.
- c) Each MAS Register is checked by Engineer-in-charge at least once a week.
- d) Cement Register is reviewed by Engineer-in-charge at least once in a month for work at same station and alternate months for work at outstation.
- e) It shall be mandatory for the field staff to retain the self-attested (by agencies / contractors) copies of Tax paid bills of the material entered in the MAS register viz, steel, cement, bitumen, paint, prime, distemper, varnishes, Tile adhesive, admixture, anti-termite chemical, water proofing compound material and any other item as decided by the NIT approving authority.
- f) Self-attested copies of Tax paid bills of material taken in MAS register shall be obtained by the field staff from the agencies/ contactors before settling the payment. In case of any doubt the same can be verified by the filed staff. However, onus of genuineness of Tax paid bills rests with the agencies/ contactors.

#### 3. Testing of Material at Site or in lab-

The contractor shall supply free of charge the sample materials required for testing and shall also bear the packing, sealing, transportation & other incidental charges. The material and its frequency to be tested shall be as per <u>CPWD</u> specifications or its relevant codes or as decided by Engineer-in-charge. **The testing charges for all samples shall be borne by the contractor.** 

#### LIST OF PREFERRED MAKES

Specification/brands names of materials (Refer materials, whichever are applicable for the scope of work) and finishes approved by the Engineer-in-Charge are listed below. However approved equivalent materials and finishes of any other specialized firms may be used, in case it is established that the brands specified below are not available in the market and subject to approval of the alternate brand by the Engineer-in-Charge (See also conditions of contract).

Sl. No.	Materials	Approved make
1	Ceramic Glazed / Rectified Ceramic Glazed / Vitrified Floor / Wall Tiles	Johnson / Somany / Kajaria / Nitco / Orientbell / AGL / Oasis / Varmora/ Hindware
2	Chequered CC Tiles	Nitco / KK / Unistone / Dalal /Advent / ABC / Krishna / Kirti Spun Pipes
3a	Bathroom CP Fittings (Bungalow)	Jaquar / Johnson / Marc / Cera / Kohler
3b	Bathroom CP Fittings (Servant Quarters, Type 1 & 2)	Prayag
4	Sanitary Wares	Hindware / Kohler / Johnson / Cera / Parryware / Jaquar
5a	Kitchen Sink (Stainless Steel) (Bungalow)	Neelkanth / Jayna / Anupam / Nirali / Cera
5b	Kitchen Sink (Stainless Steel) (Servant Quarters Type 1 & 2)	Prayag
6	PVC Tank (ISI Marked)	Sintex / Storex / Unitank / Sheetal / SPL
7	PVC Cistern	Commander / Duralite / Hindware/ Coral / SteelBird
8	Precast Cement Concrete Slab	Nitco / KK / Konkrete Products Co. / Dalal/ Kirti Spun Pipes
9	G.I. Sheet	SAIL / Tata Shakti / Jindal / Swastik
10	G.I. Pipe (ISI Marked)	Jindal Hissar / Tata / Prakash Surya / Zenith
11	G.I. Fittings (ISI Marked)	Unik / UK / Surya / Prakash
12	Structural steel Sections C, I, Tee, Angle, Flats, Bars etc. (ISI Marked)	TISCO / Jindal / SAIL / Rana / Rathi
13	TMT bars (ISI Marked)	TATA /RINL / SAIL / TISCO
14	Steel tubes hot finished welded Type	BST / Jindal / Ravindra / Surya
15	Block Board, Ply Wood, MDF Board	Century / Duro / Greenply / Merino / Action Tesa Bhutan tuff / Archid Ply /
16	Lamination Sheet / Veneer	Century / Duro / Merino / Greenlam / Bhutan tuff / Archid Ply /
17	Flush Doors	Century / Greenply / Action Tesa / Sumai (Spacewood) / Orion / Duro / Jayna Doors of Jain wood Industries / Jain Doors Pvt. Ltd. / Bhutan tuff / Archid Ply /
18	Factory made chamfered edge CC Interlocking paver Block, Kerb Stone	NITCO / KK / Konkrete/ Terra Firma / Dalal / Advent / Kirti Spun Pipes
19	Precast R.C.C. manhole & gully trap covers, frames and gratings	KK / Konkrete / Pragati
20	Fibre Glass sheet and Chajjas	Rooffit of Shiv Shakti Fiber Udhyog / Fibreways Technology / Simba
21	Acrylic washable Distemper	Berger / Nerolac / ICI / Asian / Acro
22	Acrylic Emulsion Paint / Premium Acrylic Emulsion Interior paint	Berger / Nerolac / ICI / Asian / Acro
23	Premium acrylic emulsion / Acrylic Emulsion Exterior Paint	Berger / Nerolac / ICI / Asian / Acro
24	Primer	Berger / Nerolac / ICI / Asian / Acro
25	Synthetic Enamel Paint	Berger / Nerolac / ICI / Asian / Acro
26	P.O.P.	J.K. / Laxmi / Birla / Asian Paint / Sakarni
27	Decorative Paints	Oikos / SKK / Armourcoat / Ultratech / Acro
28	Modular kitchen Accessories	Stallion / Sparkle Top / Hettich / Godrej / Hafele / Dorset / Blum / Kich / Hardueyn
29	Brass Door / Window Fittings	Sigma / Bush / Dorset / Hettich / Dorma / Hardueyn
30	Dash Fastener	Hilti / Fisher / Canon / Wuerth
31	Hydraulic Door Closer	Hardwyn / Godrej / Dorma / Dorset / Hafele

32	Lock & Latches	Godrej / Dorset / Hafele / Geze / Dorma / Hardueyn
33	White Cement based Putty	Birla Wall Care / J.K. Wall Care / Berger
34	Aluminum Sections	Jindal / Hindalco / Indalco / Indo-Alusys
35	Centrifugally Cast Iron Pipe & Fittings	Neco / Truform / Techno Sales Corporations / BIC / RPMF / SKF
36	Tempered Glass / Glass Pan	Modi Float / Saint Gobain / Asahi / Atul
37	Bevelled Edge Mirror	Atul / Saint Gobain / Modi Guard / Golden Fish
38	PTMT Fittings	Prayag / Wilson / Polytuf
39	Polymer Modified Cementitious Grout	BalEndura / Laticrete / Ferrous Crete / MAKPHALT
40	Non Shrink Cementous Grout	Xypex / Fosroc / Krytone / Ferocrete/
41	AC Pipes (Mazza)	A Infrastructure Ltd. / ApurvaVinimay Pvt. Ltd. / Kanoria Sugar Gen. Mfg. Co. Ltd.
42	Cement Board	Bison / Everest / Shalimar / NCL
43	Aluminium Composite Panels	Aludecore / Alstone / Alstrong / Alucobond / Aluco Pan / Virgo / Alutech
44	Wood Polish	Asian Paints / Pidlite Industries / ICIDulux / Wembley
45	Gypsum Board	St. Gobain / Gyproc Gypsum / Boral / Everest
46	Calcium Silicate False Ceiling System Along with supportings	Aerolite / Everest / NCL / Hilux/ Gyptech
47	All hardware and fittings other than brass for doors, windows etc.	Dorma / Hafele / Geze / Ozone / Kich / Hettich / Dorset / Hardwyn
48	Adhesive / Epoxy Grout for Floor Tiles, Marble Stone, Granite Stone etc.	Ferrous Crete / Ardex Endure (Goldstar) / Pidlite (FevimateXI) / MYKLaticrete / Weber / CICO /MAKPHALT/ Home Pride
49	Water proofing compounds	Grace / Fosroc / BASF / Pidilite / CICO / SIKA / MC Bauchemie / STP Ltd. / MAKPHALT
50	FRP Doors & Frames	Ashoo Model Arts, Selected Product Co., FiberwaysTachnology and Jayna Doors of Jain wood Industries, Jain Doors Pvt. Ltd.
51	Laminated flooring	Action Tesa / Vista / Pergo / Parador
52	Stainless Steel Railing	Kich / Dorma / Q Railing / Fitwell
53	Cement (OPC / PPC)	ACC / JK Cement / Ultratech / Shree Cement
54	Engineered wooden flooring	Mikasa (Greenlam Industries Ltd.), / Pergo / Parador / Woodart
55	Drapery Rod	Vista / MAC / Magnum
56	PVC Pipe / CPVC Pipe	Supreme / Astral / Ashirvad / Prakash / Finolex
57	Foam / Cushion	Sleepwell / Kurl-on / MM Foam
58	Fabric / Cloth for Sofa	Eden / Kundan / Bealene / GM / Velvolene and Nimoco
59	Fabric / Cloth for Curtain	G.M. Fabric / Neptune Furnishing India Pvt. Ltd. / Shri Radhika Furnishing / Jai Mahavir Textile Pvt. Ltd. / New Castle / MahavirLoomtexPvt. Ltd. / Bombay Dyeing
60	GRG false ceiling	Diamond ceilings / Gyproc (Saint Gobain) / USG Boral / Gyptech
61	Metal false Ceiling	Armstrong, Hunter Douglas, gyptech Hi-Steel.
62	APP (Atactic Polypropylene Polymer)	Shivam tar product, MAK PHALT
63	CI Valve	Deepak valve
64	U.P.V.C fitting	Kaka Industries, Rajshri Plastiwood

Note:- The weight and thickness of the material should be as per CPWD Specification / relevant IS code / manufacturer specification.

#### On non-judicial stamp paper of minimum Rs. 100

# (Guarantee offered by Bank to PMML in connection with the execution of contracts) Form of Bank Guarantee for Earnest Money Deposit / performance Guarantee / Security Deposit

۱.	Whereas the Director
	Government has further agreed to accept irrevocable Bank
	Guarantee for Rs (Rupeesonly) valid upto
	(date)* as Earnest Money Deposit from (name and address of contractor)
	(hereinafter called "the contractor") for compliance of his obligations in accordance
	with the terms and conditions of the said NIT.
	or**
	*Whereas the Director, PMML, New Delhi on behalf of the competent authority, Prime
	Ministers Museum and Library has entered into an agreement bearing number with
	(name and address of the contractor). (hereinafter called "the
	Contractor") for execution of work
	further agreed to accept an irrevocable Bank Guarantee for Rs (Rupees only)
	valid upto (date) as Performance Guarantee / security Deposit from the said
	Contractor for compliance of his obligations in accordance with the terms and conditions of the
	agreement.
2.	We, (indicate the name of the bank) (herein after referred to as "the Bank"), hereby
	undertake to pay to the Government an amount not exceeding Rs(Rupees
2	only) on demand by the Government within 10 days of the demand.
3.	We,
	and payable under this guarantee without any demur, merely on a demand from the Government stating that the amount claimed is required to meet the recoveries due or likely to be due from
	the said contractor. Any such demand made on the Bank shall, be conclusive as regards the
	amount due and payable by the Bank under this Guarantee. However, our liability under this
	guarantee shall be restricted to an amount not exceeding Rs (Rupees only)
4	We, (indicate the name of the Bank) , further undertake to pay the
•	Government any money so demanded notwithstanding any dispute or disputes raised by the
	contractor in any suit or proceeding pending before any court or Tribunal, our liability under
	this Bank Guarantee being absolute and unequivocal. The payment so made by us under this
	Bank Guarantee shall be a valid discharge of our liability for payment there under and the
	contractor shall have no claim against us for making such payment.
5.	We, (indicate the name of the Bank) further agree that the Government shall
	have the fullest liberty without our consent and without affecting in any manner our obligation
	here under to vary any of the terms and conditions of the said agreement to extend time of
	performance by the said contractor from time to time or to postpone for any time or from time
	to time any of the powers exercisable by the Government against the said contractor and to
	forbear or enforce any of the terms and conditions relating to the said agreement and we shall
	not be relieved from our liability by reason of any such variation or extension being granted to
	the said contractor or for any forbearance, act of omission on the part of the Government or any
	indulgence by the Government to the said contractor or by any such matter or thing whatsoever
	which under the law relating to sureties would, but for this provision, have effect of so relieving
	us.
f	5. We, (indicate the name of the Bank) further agree that the Government at its option
•	shall be entitled to enforce this Guarantee against the Bank as a principal debtor at the first
	shall be thinked to emistee and Contained against the Built us a principal decisi at the first

instance without proceeding against the contractor and notwithstanding any security or other

guarantee the Government may have in relation to the Contractor's liabilities.

7. This guarantee will not be discharged due to the change in the constitution of the Bank or the contractor.
We, undertake not to revoke this guarantee except with the consent of the Government in writing.
8. This Bank Guarantee shall be valid up to unless extended on demand by the Government. Notwithstanding anything mentioned above, our liability against this guarantee is restricted to Rs (Rupees only) and unless a claim in writing is lodged with us within the date of expiry or extended date of expiry of this guarantee, all our liabilities under this guarantee shall stand discharged.
Date
Witnesses:
Signature
Authorized signatory Name and address
Name Designation Staff code no.
Signature
Bank seal
Name and address

- \* Date to be worked out on the basis of validity period of 90 days where only financial bids are invited and 180 days for two / three bid system from the date of submission of tender / bid.
- \*\* In paragraph 1, strike out the portion not applicable. Bank Guarantee will be made either for earnest money or for performance guarantee / security deposit as the case may be.

# $\frac{FORM\ OF\ PERFORMANCE\ SECURITY\ (GUARANTEE)}{BANK\ GUARANTEE\ BOND}$

	In consideration of the Director, Prime Ministers the terms and conditions of the proposed agreement	t between	and
said	Contractor(s)")	for	the
Guara	(hereafter called "the said agreement") having a	agreed to production of	a irrevocable Bank for
as a se	ecurity/guarantee from the contractor(s) for compliand and conditions in the said agreement.		• '
the r	here in after name of the Bank) undertake to pay to the(RupeesOnly) on o	Government in amou	nt not exceeding
2)	We do hereby payable	y undertake to pay the	amounts due and
	(indicate the name of the Bank) under this Guarante from the Government stating that the amount claim likely to be due from the said contractor(s). Any conclusive as regards the amount due and payable our liability under this guarantee shall be rest(Rupees	ned is required to meet the such demand made on by the bank under this Grantetted to an amount re-	the Bank shall be uarantee. However,
3)	We, the said bank further undertake to pay to to notwithstanding any dispute or disputes raised by pending before any court or Tribunal relating the absolute and unequivocal.  The payment so made by us under this bond shall be	the contractor(s) in any ereto, our liability under	suit or proceeding this present being
	there under and the contractor(s) shall have no claim		
4).	We	ain in full force and effect d agreement and that it s der or by virtue of the sa d or till Engineer-in-Char s of the said agreement h	ct during the period shall continue to be aid agreement have rge on behalf of the have been fully and
5)	We	Bank) the Government shin any manner our obligatement or to extend time one for any time or from the the said contractor (s) to the said agreement antiation, or extension being sion on the part of the Caractor(s) or by any succession.	hall have the fullest ations hereunder to e of performance by time to time any of and to for bear or nd we shall not be g granted to the said Government or any ch matter or thing

0)	contractor(s).	be discharged due to the	e change in the constitution of the bank or t	ıne
7)			lastly undertake a arantee except with the previous consent of	
8)	Government. Notwithstarestricted to Rsin writing is lodged with	nding anything mention (Rs us within six months of	. Unless extended on demand led above, our liability against this guarantee only) and unless a clathe date of expiry or the extended date of exprantee shall stand discharged.	e is aim
	Dated the		of	for
			(indicate the name of bank)	

### **SCHEDULE OF QUANTITY**

Name of work: - Annual Repair work and M/o of Library building PMML campus during 2025-26(SH: Repair a replacement of old Rusted C.I pipe line in shaft etc) Teen Murti House, New Delhi	Annual Repair work and M/o of Library building PMML campus during 2025-26(SH: Repair and replacement of old Rusted C.I pipe line in shaft etc) Teen Murti House, New Delhi				

## **SCHEDULE OF QUANITY**

Name of Work: A/R & M/o to Library building PMM campus during 2025-26. (SH: Repair and replacement of old rusted C.I. pipe line in shaft.)

12.47 Providing & fixing UV stabilised fiberglass reinforced plastic sheet roofing up to any pitch, including fixing with polymer coated 'J' or 'L' hooks, bolts & nuts 8 mm dia. G.I. plain/bitumen washers complete but excluding the cost of purlins, rafters, trusses etc. The sheets shall be manufactured out of 2400 TEX panel rovigs incorporating minimum 0.3% ultra-violet stabiliser in resin system under approximately 2400 psi and hot cured. They shall be of uniform pigmentation and thickness without air pockets and shall conform to IS 0192 and IS 12866.The sheets shall be opaque or translucent, clear or pigmented, textured or smooth as specified.  12.47.1 2 mm thick corrugated (2.5" or 4.2" or 6") or step-down (2" or 3" or 6") as specified  13.6.1 1.4 (1 cement: 4 coarse sand)  5 13.46 Finishing walls with Acrylic Smooth exterior paint of required shade:  13.41.1 New work (Two or more coat applied @ 1.67 Itr/10 sqm over and including priming coat of exterior primer applied @ 0.90 litre/10 sqm)  6 13.61 Painting with synthetic enamel paint of approved brand and manufacture to give an even shade:  13.61.1 Two or more coats on new work  7 13.80 Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete.  9 14.1 Repairs to plaster of thickness 12 mm to 20 mm in patches of area 2.5 sq.meters and under, including cutting the patch in proper shape, raking out joints and preparing and plastering the surface of the walls complete, including disposal of rubbish to the dumping ground, all complete as per direction of Engineer-in-Charge.  14.1.2 With cement mortar 1:4 (3 cement: 4 coarse sand)  9 15.2 Demolishing cement concrete manually/ by mechanical means including disposal of ridbesh to richer mix (including equivalent means including disposal of richer mix (including equivalent to means including disposal of richer mix (including equivalent to means including disposal of material within 50	S.No	DSR Code	Description	Qty	unit	Rate	Amount
10.25 Steel work welded in built up sections/ framed work, including cutting, hoisting, fixing in position and applying a priming coat of approved steel primer using structural steel etc. as required.  10.25.2 In gratings, frames, guard bar, ladder, railings, brackets, gates and similar works  10.26.3 12.47 Providing & fixing UV stabilised fiberglass reinforced plastic sheet roofing up to any pitch, including fixing with polymer coated 'I' or 'L' hooks, bolts & nuts 8 mm dia. G.I plain/bitumen washers complete but excluding the cost of purlins, rafters, trusses etc. The sheets shall be manufactured out of 2400 TEX panel rovigs incorporating minimum 0.3% ultra-violet stabiliser in reisn system under approximately 2400 psi and hot cured. They shall be of uniform pigmentation and thickness without air pockets and shall conform to IS 10129 and IS 12866. The sheets shall be opaque or translucent, clear or pigmented, textured or smooth as specified.  12.47.1 2 mm thick corrugated (2.5" or 4.2" or 6") or step-down (2" or 3" or 6") as specified  13.6.1 13.4 (1 cement 4 coarse sand)  5 13.46 Finishing walls with Acrylic Smooth exterior paint of required shade:  13.6.1. New work (Two or more coat applied @ 1.67 ltr/10 sqm over and including priming coat of exterior primer applied @ 0.90 litre/10 sqm)  6 13.61 New work (Two or more coat applied @ 1.67 ltr/10 sqm over and including priming coat of exterior primer applied @ 0.90 litre/10 sqm)  7 13.80 Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacture to give an even shade:  13.6.1. Two or more coats on new work  9 15.0.5 Sqm 156.05 140456  8 14.1. Repairs to plaster of thickness 12 mm to 20 mm in patches of area 2.5 sq. meters and under, including cutting the patch in proper shape, raking out joints and preparing and plastering the surface of the walls complete, including disposal of rubbish to the dumping ground, all complete as per direction of Engineer-in-Charge.  14.1.2 With cement mortar 1:4 (1cement: 4 coarse				-			
10.25   Steel work welded in built up sections/ framed work, including cutting, holsting, fixing in position and applying a priming coat of approved steel primer using structural steel etc. as required.     10.25.2   In gratings, frames, guard bar, ladder, railings, brackets, gates and similar works gates and similar works     10.05   2   To gratings, frames, guard bar, ladder, railings, brackets, gates and similar works     10.00   kg   172.60   172600     10.26   To 'L' hooks, botts & nuts & mm dia. G.I. plain/bitumen washers complete but excluding the cost of purlins, rafters, trusses etc. The sheets shall be manufactured out of 2400 TEX panel rovings incorporating minimum 0.3% ultra-violet stabiliser in resin system under approximately 2400 psi and hot cured. They shall be of uniform pigmentation and thickness without air pockets and shall conform to Is 10192 and IS 12866. The sheets shall be opaque or translucent, clear or pigmented, textured or smooth as specified.    12.47.1   2 mm thick corrugated (2.5" or 4.2" or 6") or step-down (2" or 3" or 6") as specified    13.6.1   1.4 (1 cement: 4 coarse sand)   150   Sqm   1401.35   210203				300	cum	294.96	88488
including cutting, hoisting, fixing in position and applying a priming coat of approved steel primer using structural steel etc. as required.  10.25.2 In gratings, frames, guard bar, ladder, railings, brackets, gates and similar works  12.47 Providing & fixing UV stabilised fiberglass reinforced plastic sheet roofing up to any pitch, including fixing with polymer coated 'J' or 'L' hooks, bolts & nuts 8 mm dia. G.I plain/bitumen washers complete but excluding the cost of purlins, rafters, trusses etc. The sheets shall be manufactured out of 2400 TEX panel rovigs incorporating minimum 0.3% ultra-violet stabiliser in resin system under approximately 2400 psi and hot cured. They shall be of uniform pigmentation and thickness without air pockets and shall conform to IS 10192 and IS 12866. The sheets shall be opaque or translucent, clear or pigmented, textured or smooth as specified.  12.47.1 2 mm thick corrugated (2.5" or 4.2" or 6") or step-down (2" or 3" or 6") as specified.  2 mm thick corrugated (2.5" or 4.2" or 6") or step-down (2" or 3" or 6") as specified.  13.61.1 1:4 (1 cement: 4 coarse sand)  5 13.46.1 New work (Two or more coat applied @ 1.67 ltr/10 sqm over and including priming coat of exterior primer applied @ 0.9.09 litre/10 sqm)  6 13.61.1 New work (Two or more coat applied @ 1.67 ltr/10 sqm over and including priming coat of exterior primer applied @ 0.9.01 ltr/10 sqm over and including priming coat of exterior primer applied @ 0.9.01 ltr/10 sqm over and including priming coat of exterior primer applied go 0.90 ltr/10 sqm over and including and applying white cement based putty of average thickness 12 mm, of approved brand and manufacture to give an even shade:  13.61.1 Two or more coats on new work  7 13.80 Providing and applying white cement based putty of average thickness 12 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete.  8 14.1 Repairs to plaster of thickness 12 mm to 20 mm in patches of area 2.5 sq.meters and under, incl	2	10.25					
priming coat of approved steel primer using structural steel etc. as required.  10.25.2 In gratings, frames, guard bar, ladder, railings, brackets, gates and similar works  1000 kg 172.60 172600  12.47 Providing & fixing UV stabilised fiberglass reinforced plastic sheet roofing up to any pitch, including fixing with polymer coated 'J' or 'L' hooks, bolts & nuts 8 mm dia. G.I plain/bitumen washers complete but excluding the cost of purlins, rafters, trusses etc. The sheets shall be manufactured out of 2400 TEX panel rovigs incorporating minimum 0.3% ultra-violet stabiliser in resin system under approximately 2400 psi and hot cured. They shall be of uniform pigmentation and thickness without air pockets and shall conform to Is 10192 and Is 12866. The sheets shall be opaque or translucent, clear or pigmented, textured or smooth as specified.  12.47.1 2 mm thick corrugated (2.5" or 4.2" or 6") or step-down (2" or 3" or 6") as specified so or 3" or 6") as specified 50 mm cement plaster of mix: 600 Sqm 487.40 292440 finishing walls with Acrylic Smooth exterior paint of required shade:  13.61 11.4 (1 cement: 4 coarse sand) 600 Sqm 487.40 292440 finishing walls with Acrylic Smooth exterior paint of required shade:  13.61.1 New work (Two or more coat applied 6 1.67 Itr/10 sqm over and including priming coat of exterior primer applied 6 0.90 litre/10 sqm) 900 Sqm 160.60 144540 900 Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacture to give an even shade:  13.61.1 Two or more coats on new work 900 Sqm 156.05 140445 91 average thickness 1 mm, of approved brand and manufacture to give an even shade:  14.1.2 Repairs to plaster of thickness 12 mm to 20 mm in patches of area 2.5 sq.meters and under, including cutting the patch in proper shape, raking out joints and preparing and plastering the surface of the walls complete, including disposal of rubbish to the dumping ground, all complete as per direction of Engineer-in-Charge.  14.1.2 With cement mortar 1:4 (Icement: 4			•				
etc. as required.  10.25.2 In gratings, frames, guard bar, ladder, railings, brackets, gates and similar works  10.00 kg 172.60 172600  12.47 Providing & fixing UV stabilised fiberglass reinforced plastic sheet roofing up to any pitch, including fixing with polymer coated '1' or '1' hooks, bolts & nuts 8 mm dia. G. I plain/bitumen washers complete but excluding the cost of purlins, rafters, trusses etc. The sheets shall be manufactured out of 2400 TEX panel rovigs incorporating minimum 0.3% ultra-violet stabiliser in resin system under approximately 2400 psi and hot cured. They shall be of uniform pigmentation and thickness without air pockets and shall conform to IS 10192 and IS 12866. The sheets shall be opaque or translucent, clear or pigmented, textured or smooth as specified.  12.47.1 2 mm thick corrugated (2.5" or 4.2" or 6") or step-down (2" or 3" or 6") as specified.  13.61.1 1.4 (1 cement: 4 coarse sand) 600 Sqm 487.40 292440 and 13.6 20 mm cement plaster of mix:  13.61.1 1.4 (1 cement: 4 coarse sand) 600 Sqm 487.40 292440 from the coarse of sand shade:  13.46.1 1.3.61 Painting walls with Acrylic Smooth exterior paint of required shade:  13.61.1 Two or more coat applied @ 1.67 ltr/10 sqm over and including priming coat of exterior primer applied @ 0.90 litre/10 sqm) 900 Sqm 160.60 144540 and manufacture to give an even shade:  13.61.1 Two or more coats on new work  7 13.80 Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete.  8 14.1 Repairs to plaster of thickness 12 mm to 20 mm in patches of area 2.5 sq. meters and under, including cutting the patch in proper shape, raking out joints and preparing and plastering the surface of the walls complete, including disposal of rubbish to the dumping ground, all complete as per direction of Engineer-in-charge.  14.1.2 With cement mortar 1:4 (1cement: 4 coarse sand) 300 Sqm 560.50 168150 meters lead as per direction of Engine							
10.25.2 In gratings, frames, guard bar, ladder, raillings, brackets, gates and similar works Providing & fixing UV stabilised fiberglass reinforced plastic sheet roofing up to any pitch, including fixing with polymer coated '1' or '1' hooks, bolts & nuts 8 mm dia. G.I plain/bitumen washers complete but excluding the cost of purlins, rafters, trusses etc. The sheets shall be manufactured out of 2400 TEX panel rovigs incorporating minimum o.3% ultra-violet stabiliser in resin system under approximately 2400 psi and hot cured. They shall be of uniform pigmentation and thickness without air pockets and shall conform to 15 10192 and 15 12866. The sheets shall be opaque or translucent, clear or pigmented, textured or smooth as specified.  12.47.1 2 mm thick corrugated (2.5" or 4.2" or 6") or step-down (2" or 3" or 6") as specified.  13.6.1 20 mm cement plaster of mix:  13.6.1 1:4 (1 cement: 4 coarse sand)  5 13.46 Finishing walls with Acrylic Smooth exterior paint of required shade:  13.46.1 New work (Two or more coat applied @ 1.67 ltr/10 sqm over and including priming coat of exterior primer applied @ 0.90 litre/10 sqm)  13.61 Painting with synthetic enamel paint of approved brand and manufacture to give an even shade:  13.61.1 Two or more coats on new work  7 13.80 Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete.  8 14.1 Repairs to plaster of thickness 12 mm to 20 mm in patches of area 2.5 sq.meters and under, including cutting the patch in proper shape, raking out joints and preparing and plastering the surface of the walls complete, including disposal of rubbish to the dumping ground, all complete as per direction of Engineer-in-Charge.  14.1.2 With cement mortar 1:4 (1cement: 4 coarse sand) 300 Sqm 560.50 168150 means including disposal of rubbish to the dumping ground, all complete as per direction of Engineer-in-Charge.  15.2.1 Nominal concrete 1:3:6 or richer mix (inc			I				
12.47   Providing & fixing UV stabilised fiberglass reinforced plastic sheet roofing up to any pitch, including fixing with polymer coated '1' or '1' hooks, bolts & nuts 8 mm dia. G.I plain/bitumen washers complete but excluding the cost of purlins, rafters, trusses etc. The sheets shall be manufactured out of 2400 TEX panel rovigs incorporating minimum 0.3% ultra-violet stabiliser in resin system under approximately 2400 psi and hot cured. They shall be of uniform pigmentation and thickness without air pockets and shall conform to IS 10192 and IS 12866.The sheets shall be opaque or translucent, clear or pigmented, textured or smooth as specified.    12.47.1		10.25.2					
12.47 Providing & fixing UV stabilised fiberglass reinforced plastic sheet roofing up to any pitch, including fixing with polymer coated 'J' or 'L' hooks, bolts & nuts 8 mm dia. G.I. plain/bitumen washers complete but excluding the cost of purlins, rafters, trusses etc. The sheets shall be manufactured out of 2400 TEX panel rovigs incorporating minimum 0.3% ultra-violet stabiliser in resin system under approximately 2400 psi and hot cured. They shall be of uniform pigmentation and thickness without air pockets and shall conform to IS 10192 and IS 12866.The sheets shall be opaque or translucent, clear or pigmented, textured or smooth as specified.  12.47.1 2 mm thick corrugated (2.5" or 4.2" or 6") or step-down (2" or 3" or 6") as specified  13.6.1 1.4 (1 cement: 4 coarse sand)  5 13.46 Finishing walls with Acrylic Smooth exterior paint of required shade:  13.41.1 New work (Two or more coat applied @ 1.67 Itr/10 sqm over and including priming coat of exterior primer applied @ 0.90 litre/10 sqm)  6 13.61 Painting with synthetic enamel paint of approved brand and manufacture to give an even shade:  13.61.1 Two or more coats on new work  7 13.80 Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete.  90.0 Sqm 155.90 46770  7 13.80 Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete.  90.0 Sqm 156.05 140445  8 14.1 Repairs to plaster of thickness 12 mm to 20 mm in patches of area 2.5 sq. meters and under, including cutting the patch in proper shape, raking out joints and preparing and plastering the surface of the walls complete, including disposal of rubbish to the dumping ground, all complete as per direction of Engineer-in-Charge.  14.1.2 With cement mortar 1:4 (3 cement: 4 coarse sand) 300 Sqm 560.50 168150  9 15.2 Demolishing cement concret				1000	kg	172.60	172600
sheet roofing up to any pitch, including fixing with polymer coated '1' or 'L' hooks, botts & nuts & mm dia. G.I plain/bitumen washers complete but excluding the cost of purlins, rafters, trusses etc. The sheets shall be manufactured out of 2400 TEX panel rovigs incorporating minimum 0.3% ultra-violet stabiliser in resin system under approximately 2400 psi and hot cured. They shall be of uniform pigmentation and thickness without air pockets and shall conform to IS 10192 and IS 12866. The sheets shall be opaque or translucent, clear or pigmented, textured or smooth as specified or 3" or 6") as specified 15.0 Sqm 1401.35 210203 12.47.1 2 mm thick corrugated (2.5" or 4.2" or 6") or step-down (2" or 3" or 6") as specified 13.6.1 1:4 (1 cement: 4 coarse sand) 600 Sqm 487.40 292440 13.6.1 1:4 (1 cement: 4 coarse sand) 600 Sqm 487.40 292440 13.6.1 New work (Two or more coat applied @ 1.67 ltr/10 sqm over and including priming coat of exterior primer applied @ 0.90 ltr/10 sqm) over and including priming coat of exterior primer applied @ 0.90 ltr/10 sqm) 900 Sqm 160.60 144540 13.61.1 Two or more coats on new work 14.7 Two or more coats on new work 15.5.90 Sqm 155.90 46770 13.80 Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacture, over the plastered wall surface to prepare the surface even and smooth complete. 900 Sqm 156.05 140445 14.1 Repairs to plaster of thickness 12 mm to 20 mm in patches of area 2.5 sq. meters and under, including cutting the patch in proper shape, raking out joints and preparing and plastering the surface	3	12.47					
coated 'J' or 'L' hooks, bolts & nuts 8 mm dia. G.I plain/bitumen washers complete but excluding the cost of purlins, rafters, trusses etc. The sheets shall be manufactured out of 2400 TEX panel rovigs incorporating minimum 0.3% ultra-violet stabiliser in resin system under approximately 2400 psi and hot cured. They shall be of uniform pigmentation and thickness without air pockets and shall conform to IS 10192 and IS 12866.The sheets shall be opaque or translucent, clear or pigmented, textured or smooth as specified.  12.47.1 2 mm thick corrugated (2.5" or 4.2" or 6") or step-down (2" or 3" or 6") as specified  2 mm cement plaster of mix: 2 mm thick corrugated (2.5" or 4.2" or 6") or step-down (2" or 3" or 6") as specified  3 13.6.1 1.4 (1 cement: 4 coarse sand)  5 13.46 Finishing walls with Acrylic Smooth exterior paint of required shade:  13.41.1 New work (Two or more coat applied @ 1.67 ltr/10 sqm over and including priming coat of exterior primer applied @ 0.90 litre/10 sqm)  6 13.61 Painting with synthetic enamel paint of approved brand and manufacture to give an even shade:  13.61.1 Two or more coats on new work  300 Sqm 160.60 144540  7 13.80 Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete.  8 14.1 Repairs to plaster of thickness 12 mm to 20 mm in patches of area 2.5 sq.meters and under, including cutting the patch in proper shape, raking out joints and preparing and plastering the surface of the walls complete, including disposal of rubbish to the dumping ground, all complete as per direction of Engineer-in-Charge.  14.1.2 With cement mortar 1.4 (1cement: 4 coarse sand)  300 Sqm 560.50 168150  15.2.1 Wominal concrete 1:3:6 or richer mix (including equivalent							
plain/bitumen washers complete but excluding the cost of purlins, rafters, trusses etc. The sheets shall be manufactured out of 2400 TEX panel rovigs incorporating minimum 0.3% ultra-violet stabiliser in resin system under approximately 2400 psi and hot cured. They shall be of uniform pigmentation and thickness without air pockets and shall conform to Is 10192 and Is 12866.The sheets shall be opaque or translucent, clear or pigmented, textured or smooth as specified.  12.47.1 2 mm thick corrugated (2.5" or 4.2" or 6") or step-down (2" or 3" or 6") as specified  13.6 20 mm cement plaster of mix:  13.6.1 1:4 (1 cement: 4 coarse sand)  5 13.46 Finishing walls with Acrylic Smooth exterior paint of required shade:  New work (Two or more coat applied @ 1.67 ltr/10 sqm over and including priming coat of exterior primer applied @ 0.90 litre/10 sqm)  over and including priming coat of exterior primer applied and manufacture to give an even shade:  13.6.1.1 Two or more coats on new work  7 13.80 Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete.  8 14.1 Repairs to plaster of thickness 12 mm to 20 mm in patches of area 2.5 sq.meters and under, including cutting the patch in proper shape, raking out joints and preparing and plastering the surface of the walls complete, including disposal of rubbish to the dumping ground, all complete as per direction of Engineer-in-Charge.  14.1.2 With cement mortar 1:4 (1cement: 4 coarse sand)  300 Sqm 560.50 168150  9 15.2 Demolishing cement concrete manually/ by mechanical means including disposal of material within 50 metres lead as per direction of Engineer - in - charge.  15.2.1 Nominal concrete 1:3:6 or richer mix (including equivalent							
purlins, rafters, trusses etc. The sheets shall be manufactured out of 2400 TEX panel rovigs incorporating minimum 0.3% ultra-violet stabiliser in resin system under approximately 2400 psi and hot cured. They shall be of uniform pigmentation and thickness without air pockets and shall conform to IS 10.192 and IS 1.2866.The sheets shall be opaque or translucent, clear or pigmented, textured or smooth as specified.  12.47.1 2 mm thick corrugated (2.5" or 4.2" or 6") or step-down (2" or 3" or 6") as specified.  13.6.1 1.4 (1 cement: 4 coarse sand) foo Sqm 1401.35 210203 13.6.1 1.4 (1 cement: 4 coarse sand) foo Sqm 487.40 292440 13.6.1 1.4 (1 cement: 4 coarse sand) foo Sqm 487.40 292440 13.6.1 1.4 (1 cement: 4 coarse sand) foo Sqm 487.40 292440 13.6.1 New work (Two or more coat applied © 1.67 ltr/10 sqm over and including priming coat of exterior primer applied © 0.90 litre/10 sqm) for required shade:  13.6.1 1 Two or more coats on new work for paint of approved brand and manufacture to give an even shade:  13.6.1 1 Two or more coats on new work for providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete. for example the patch in proper shape, raking out joints and preparing and plastering the surface of the walls complete, including disposal of rubbish to the dumping ground, all complete as per direction of Engineer-in-Charge.  14.1.2 With cement mortar 1:4 (1cement: 4 coarse sand) 300 Sqm 560.50 168150 for part direction of Engineer in charge.			·				
manufactured out of 2400 TEX panel rovigs incorporating minimum 0.3% ultra-violet stabiliser in resin system under approximately 2400 psi and hot cured. They shall be of uniform pigmentation and thickness without air pockets and shall conform to IS 10192 and IS 12866. The sheets shall be opaque or translucent, clear or pigmented, textured or smooth as specified.  12.47.1 2 mm thick corrugated (2.5" or 4.2" or 6") or step-down (2" or 3" or 6") as specified  13.6.1 20 mm cement plaster of mix:  13.6.1 13.40 1 finishing walls with Acrylic Smooth exterior paint of required shade:  13.46.1 New work (Two or more coat applied @ 1.67 ltr/10 sqm over and including priming coat of exterior primer applied @ 0.90 litre/10 sqm)  6 13.61 Painting with synthetic enamel paint of approved brand and manufacture to give an even shade:  13.61.1 Two or more coats on new work  13.61.2 Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete.  8 14.1 Repairs to plaster of thickness 12 mm to 20 mm in patches of area 2.5 sq.meters and under, including cutting the patch in proper shape, raking out joints and preparing and plastering the surface of the walls complete, including disposal of rubbish to the dumping ground, all complete as per direction of Engineer-in-Charge.  14.1.2 With cement mortar 1:4 (1cement: 4 coarse sand)  9 15.2 Demolishing cement concrete manually/ by mechanical means including disposal of material within 50 metres lead as per direction of Engineer - in - charge.							
minimum 0.3% ultra-violet stabiliser in resin system under approximately 2400 psi and hot cured. They shall be of uniform pigmentation and thickness without air pockets and shall conform to IS 10192 and IS 12866. The sheets shall be opaque or translucent, clear or pigmented, textured or smooth as specified.  12.47.1 2 mm thick corrugated (2.5" or 4.2" or 6") or step-down (2" or 3" or 6") as specified 150 Sqm 1401.35 210203  4 13.6 20 mm cement plaster of mix: 13.6.1 1:4 (1 cement: 4 coarse sand) 600 Sqm 487.40 292440  5 13.46 Finishing walls with Acrylic Smooth exterior paint of required shade: 13.46.1 New work (Two or more coat applied @ 1.67 ltr/10 sqm over and including priming coat of exterior primer applied @ 0.90 litre/10 sqm)  6 13.61 Painting with synthetic enamel paint of approved brand and manufacture to give an even shade: 300 Sqm 155.90 46770  7 13.80 Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete. 900 Sqm 156.05 140445  8 14.1 Repairs to plaster of thickness 12 mm to 20 mm in patches of area 2.5 sq.meters and under, including cutting the patch in proper shape, raking out joints and preparing and plastering the surface of the walls complete, including disposal of rubbish to the dumping ground, all complete as per direction of Engineer-in-Charge.  14.1.2 With cement mortar 1:4 (1cement: 4 coarse sand) 300 Sqm 560.50 168150  9 15.2 Demolishing cement concrete manually/ by mechanical means including disposal of material within 50 metres lead as per direction of Engineer - in - charge.							
approximately 2400 psi and hot cured. They shall be of uniform pigmentation and thickness without air pockets and shall conform to IS 10192 and IS 12866.The sheets shall be opaque or translucent, clear or pigmented, textured or smooth as specified.  12.47.1 2 mm thick corrugated (2.5" or 4.2" or 6") or step-down (2" or 3" or 6") as specified  13.6.1 2.4 (1 cement: 4 coarse sand)  5 13.46 Finishing walls with Acrylic Smooth exterior paint of required shade:  13.46.1 New work (Two or more coat applied @ 1.67 ltr/10 sqm over and including priming coat of exterior primer applied @ 0.90 litre/10 sqm)  900 Sqm 160.60 144540  13.61.1 Two or more coats on new work  13.61.1 Two or more coats on new work  13.80 Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete.  8 14.1 Repairs to plaster of thickness 12 mm to 20 mm in patches of area 2.5 sq.meters and under, including cutting the patch in proper shape, raking out joints and preparing and plastering the surface of the walls complete, including disposal of rubbish to the dumping ground, all complete as per direction of Engineer-in-Charge.  14.1.2 With cement mortar 1:4 (1cement: 4 coarse sand)  9 15.2 Demolishing cement concrete manually/ by mechanical means including disposal of material within 50 metres lead as per direction of Engineer in - charge.							
uniform pigmentation and thickness without air pockets and shall conform to IS 10192 and IS 12866.The sheets shall be opaque or translucent, clear or pigmented, textured or smooth as specified.  12.47.1 2 mm thick corrugated (2.5" or 4.2" or 6") or step-down (2" or 3" or 6") as specified  13.6 20 mm cement plaster of mix:  13.6.1 1:4 (1 cement: 4 coarse sand)  5 13.46 Finishing walls with Acrylic Smooth exterior paint of required shade:  13.46.1 New work (Two or more coat applied @ 1.67 ltr/10 sqm over and including priming coat of exterior primer applied @ 0.90 litre/10 sqm over and including priming coat of exterior primer applied @ 0.90 litre/10 sqm over and including and applying white cement based putty of average thickness 1 mm, of approved brand and manufacture to give an even shade:  13.61.1 Two or more coats on new work  7 13.80 Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete.  8 14.1 Repairs to plaster of thickness 12 mm to 20 mm in patches of area 2.5 sq.meters and under, including cutting the patch in proper shape, raking out joints and preparing and plastering the surface of the walls complete, including disposal of rubbish to the dumping ground, all complete as per direction of Engineer-in-Charge.  14.1.2 With cement mortar 1:4 (1cement: 4 coarse sand)  15.2.1 Nominal concrete 1:3:6 or richer mix (including equivalent							
and shall conform to IS 10192 and IS 12866. The sheets shall be opaque or translucent, clear or pigmented, textured or smooth as specified.  12.47.1 2 mm thick corrugated (2.5" or 4.2" or 6") or step-down (2" or 3" or 6") as specified 150 Sqm 1401.35 210203  4 13.6 20 mm cement plaster of mix:  13.6.1 1:4 (1 cement: 4 coarse sand) 600 Sqm 487.40 292440  5 13.46 Finishing walls with Acrylic Smooth exterior paint of required shade:  New work (Two or more coat applied @ 1.67 ltr/10 sqm over and including priming coat of exterior primer applied @ 0.90 litre/10 sqm) 900 Sqm 160.60 144540  6 13.61 Two or more coats on new work 300 Sqm 155.90 46770  7 13.80 Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete. 900 Sqm 156.05 140445  8 14.1 Repairs to plaster of thickness 12 mm to 20 mm in patches of area 2.5 sq. meters and under, including cutting the patch in proper shape, raking out joints and preparing and plastering the surface of the walls complete, including disposal of rubbish to the dumping ground, all complete as per direction of Engineer-in-Charge.  14.1.2 With cement mortar 1:4 (1cement: 4 coarse sand) 300 Sqm 560.50 168150  9 15.2 Demolishing cement concrete manually/ by mechanical means including disposal of material within 50 metres lead as per direction of Engineer- in - charge.  15.2.1 Nominal concrete 1:3:6 or richer mix (including equivalent			1				
be opaque or translucent, clear or pigmented, textured or smooth as specified.  12.47.1 2 mm thick corrugated (2.5" or 4.2" or 6") or step-down (2" or 3" or 6") as specified  13.6 2							
smooth as specified.  12.47.1 2 mm thick corrugated (2.5" or 4.2" or 6") or step-down (2" or 3" or 6") as specified  13.6.1 20 mm cement plaster of mix:  13.6.1 1:4 (1 cement: 4 coarse sand) 600 Sqm 487.40 292440  5 13.46 Finishing walls with Acrylic Smooth exterior paint of required shade:  13.46.1 New work (Two or more coat applied @ 1.67 ltr/10 sqm over and including priming coat of exterior primer applied @ 0.90 litre/10 sqm)  900 Sqm 160.60 144540  6 13.61 Painting with synthetic enamel paint of approved brand and manufacture to give an even shade:  13.61.1 Two or more coats on new work  7 13.80 Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete.  8 14.1 Repairs to plaster of thickness 12 mm to 20 mm in patches of area 2.5 sq.meters and under, including cutting the patch in proper shape, raking out joints and preparing and plastering the surface of the walls complete, including disposal of rubbish to the dumping ground, all complete as per direction of Engineer-in-Charge.  14.1.2 With cement mortar 1:4 (1 cement: 4 coarse sand)  9 15.2 Demolishing cement concrete manually/ by mechanical means including disposal of material within 50 metres lead as per direction of Engineer - in - charge.  15.2.1 Nominal concrete 1:3:6 or richer mix (including equivalent							
or 3" or 6") as specified  13.6 20 mm cement plaster of mix:  13.6.1 1:4 (1 cement: 4 coarse sand)  5 13.46 Finishing walls with Acrylic Smooth exterior paint of required shade:  13.46.1 New work (Two or more coat applied @ 1.67 ltr/10 sqm over and including priming coat of exterior primer applied @ 0.90 litre/10 sqm)  900 Sqm 160.60 144540  6 13.61 Painting with synthetic enamel paint of approved brand and manufacture to give an even shade:  13.61.1 Two or more coats on new work  7 13.80 Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete.  8 14.1 Repairs to plaster of thickness 12 mm to 20 mm in patches of area 2.5 sq.meters and under, including cutting the patch in proper shape, raking out joints and preparing and plastering the surface of the walls complete, including disposal of rubbish to the dumping ground, all complete as per direction of Engineer-in-Charge.  14.1.2 With cement mortar 1:4 (1cement: 4 coarse sand)  9 15.2 Demolishing cement concrete manually/ by mechanical means including disposal of material within 50 metres lead as per direction of Engineer - in - charge.  15.2.1 Nominal concrete 1:3:6 or richer mix (including equivalent							
or 3" or 6") as specified  13.6 20 mm cement plaster of mix:  13.6.1 1:4 (1 cement: 4 coarse sand)  5 13.46 Finishing walls with Acrylic Smooth exterior paint of required shade:  13.46.1 New work (Two or more coat applied @ 1.67 ltr/10 sqm over and including priming coat of exterior primer applied @ 0.90 litre/10 sqm)  900 Sqm 160.60 144540  6 13.61 Painting with synthetic enamel paint of approved brand and manufacture to give an even shade:  13.61.1 Two or more coats on new work  7 13.80 Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete.  8 14.1 Repairs to plaster of thickness 12 mm to 20 mm in patches of area 2.5 sq.meters and under, including cutting the patch in proper shape, raking out joints and preparing and plastering the surface of the walls complete, including disposal of rubbish to the dumping ground, all complete as per direction of Engineer-in-Charge.  14.1.2 With cement mortar 1:4 (1cement: 4 coarse sand)  9 15.2 Demolishing cement concrete manually/ by mechanical means including disposal of material within 50 metres lead as per direction of Engineer - in - charge.  15.2.1 Nominal concrete 1:3:6 or richer mix (including equivalent		12.47.1	2 mm thick corrugated (2.5" or 4.2" or 6") or step-down (2"			9	
4 13.6 20 mm cement plaster of mix: 13.6.1 1:4 (1 cement: 4 coarse sand) 600 Sqm 487.40 292440 5 13.46 Finishing walls with Acrylic Smooth exterior paint of required shade: 13.46.1 New work (Two or more coat applied @ 1.67 ltr/10 sqm over and including priming coat of exterior primer applied @ 0.90 litre/10 sqm) 900 Sqm 160.60 144540 6 13.61 Painting with synthetic enamel paint of approved brand and manufacture to give an even shade: 13.61.1 Two or more coats on new work 300 Sqm 155.90 46770 7 13.80 Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete. 900 Sqm 156.05 140445 8 14.1 Repairs to plaster of thickness 12 mm to 20 mm in patches of area 2.5 sq.meters and under, including cutting the patch in proper shape, raking out joints and preparing and plastering the surface of the walls complete, including disposal of rubbish to the dumping ground, all complete as per direction of Engineer-in-Charge.  14.1.2 With cement mortar 1:4 (1cement: 4 coarse sand) 300 Sqm 560.50 168150 9 15.2 Demolishing cement concrete manually/ by mechanical means including disposal of material within 50 metres lead as per direction of Engineer - in - charge. 15.2.1 Nominal concrete 1:3:6 or richer mix (including equivalent				150	Sqm	1401.35	210203
13.6.1 1:4 (1 cement: 4 coarse sand) 600 Sqm 487.40 292440  5 13.46 Finishing walls with Acrylic Smooth exterior paint of required shade:  13.46.1 New work (Two or more coat applied @ 1.67 ltr/10 sqm over and including priming coat of exterior primer applied @ 0.90 litre/10 sqm) 900 Sqm 160.60 144540  6 13.61 Painting with synthetic enamel paint of approved brand and manufacture to give an even shade:  13.61.1 Two or more coats on new work 300 Sqm 155.90 46770  7 13.80 Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete. 900 Sqm 156.05 140445  8 14.1 Repairs to plaster of thickness 12 mm to 20 mm in patches of area 2.5 sq.meters and under, including cutting the patch in proper shape, raking out joints and preparing and plastering the surface of the walls complete, including disposal of rubbish to the dumping ground, all complete as per direction of Engineer-in-Charge.  14.1.2 With cement mortar 1:4 (1cement: 4 coarse sand) 300 Sqm 560.50 168150  9 15.2 Demolishing cement concrete manually/ by mechanical means including disposal of material within 50 metres lead as per direction of Engineer - in - charge.  Nominal concrete 1:3:6 or richer mix (including equivalent	4	13.6			•		
required shade:  13.46.1 New work (Two or more coat applied @ 1.67 ltr/10 sqm over and including priming coat of exterior primer applied @ 0.90 litre/10 sqm)  6 13.61 Painting with synthetic enamel paint of approved brand and manufacture to give an even shade:  13.61.1 Two or more coats on new work  7 13.80 Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete.  8 14.1 Repairs to plaster of thickness 12 mm to 20 mm in patches of area 2.5 sq.meters and under, including cutting the patch in proper shape, raking out joints and preparing and plastering the surface of the walls complete, including disposal of rubbish to the dumping ground, all complete as per direction of Engineer-in-Charge.  14.1.2 With cement mortar 1:4 (1cement: 4 coarse sand)  9 15.2 Demolishing cement concrete manually/ by mechanical means including disposal of material within 50 metres lead as per direction of Engineer - in - charge.  15.2.1 Nominal concrete 1:3:6 or richer mix (including equivalent		13.6.1		600	Sqm	487.40	292440
required shade:  13.46.1 New work (Two or more coat applied @ 1.67 ltr/10 sqm over and including priming coat of exterior primer applied @ 0.90 litre/10 sqm)  6 13.61 Painting with synthetic enamel paint of approved brand and manufacture to give an even shade:  13.61.1 Two or more coats on new work  7 13.80 Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete.  8 14.1 Repairs to plaster of thickness 12 mm to 20 mm in patches of area 2.5 sq.meters and under, including cutting the patch in proper shape, raking out joints and preparing and plastering the surface of the walls complete, including disposal of rubbish to the dumping ground, all complete as per direction of Engineer-in-Charge.  14.1.2 With cement mortar 1:4 (1cement: 4 coarse sand)  9 15.2 Demolishing cement concrete manually/ by mechanical means including disposal of material within 50 metres lead as per direction of Engineer - in - charge.  15.2.1 Nominal concrete 1:3:6 or richer mix (including equivalent	5	13.46			•		
over and including priming coat of exterior primer applied @ 0.90 litre/10 sqm)  900 Sqm 160.60 144540  13.61 Painting with synthetic enamel paint of approved brand and manufacture to give an even shade:  13.61.1 Two or more coats on new work  300 Sqm 155.90 46770  7 13.80 Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete.  900 Sqm 156.05 140445  8 14.1 Repairs to plaster of thickness 12 mm to 20 mm in patches of area 2.5 sq.meters and under, including cutting the patch in proper shape, raking out joints and preparing and plastering the surface of the walls complete, including disposal of rubbish to the dumping ground, all complete as per direction of Engineer-in-Charge.  14.1.2 With cement mortar 1:4 (1cement: 4 coarse sand)  300 Sqm 560.50 168150  9 15.2 Demolishing cement concrete manually/ by mechanical means including disposal of material within 50 metres lead as per direction of Engineer - in - charge.  15.2.1 Nominal concrete 1:3:6 or richer mix (including equivalent			required shade :				
over and including priming coat of exterior primer applied @ 0.90 litre/10 sqm)  900 Sqm 160.60 144540  13.61 Painting with synthetic enamel paint of approved brand and manufacture to give an even shade:  13.61.1 Two or more coats on new work  300 Sqm 155.90 46770  7 13.80 Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete.  900 Sqm 156.05 140445  8 14.1 Repairs to plaster of thickness 12 mm to 20 mm in patches of area 2.5 sq.meters and under, including cutting the patch in proper shape, raking out joints and preparing and plastering the surface of the walls complete, including disposal of rubbish to the dumping ground, all complete as per direction of Engineer-in-Charge.  14.1.2 With cement mortar 1:4 (1cement: 4 coarse sand)  300 Sqm 560.50 168150  9 15.2 Demolishing cement concrete manually/ by mechanical means including disposal of material within 50 metres lead as per direction of Engineer - in - charge.  15.2.1 Nominal concrete 1:3:6 or richer mix (including equivalent		13.46.1	New work (Two or more coat applied @ 1.67 ltr/10 sqm				
13.61 Painting with synthetic enamel paint of approved brand and manufacture to give an even shade:  13.61.1 Two or more coats on new work  7 13.80 Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete.  8 14.1 Repairs to plaster of thickness 12 mm to 20 mm in patches of area 2.5 sq.meters and under, including cutting the patch in proper shape, raking out joints and preparing and plastering the surface of the walls complete, including disposal of rubbish to the dumping ground, all complete as per direction of Engineer-in-Charge.  14.1.2 With cement mortar 1:4 (1cement: 4 coarse sand)  300 Sqm 560.50 168150  9 15.2 Demolishing cement concrete manually/ by mechanical means including disposal of material within 50 metres lead as per direction of Engineer - in - charge.  15.2.1 Nominal concrete 1:3:6 or richer mix (including equivalent							
and manufacture to give an even shade:  13.61.1 Two or more coats on new work  300 Sqm 155.90 46770  13.80 Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete.  900 Sqm 156.05 140445  8 14.1 Repairs to plaster of thickness 12 mm to 20 mm in patches of area 2.5 sq.meters and under, including cutting the patch in proper shape, raking out joints and preparing and plastering the surface of the walls complete, including disposal of rubbish to the dumping ground, all complete as per direction of Engineer-in-Charge.  14.1.2 With cement mortar 1:4 (1cement: 4 coarse sand)  300 Sqm 560.50 168150  9 15.2 Demolishing cement concrete manually/ by mechanical means including disposal of material within 50 metres lead as per direction of Engineer - in - charge.  15.2.1 Nominal concrete 1:3:6 or richer mix (including equivalent			@ 0.90 litre/10 sqm)	900	Sqm	160.60	144540
13.61.1 Two or more coats on new work  13.80 Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete.  900 Sqm 156.05 140445  14.11 Repairs to plaster of thickness 12 mm to 20 mm in patches of area 2.5 sq.meters and under, including cutting the patch in proper shape, raking out joints and preparing and plastering the surface of the walls complete, including disposal of rubbish to the dumping ground, all complete as per direction of Engineer-in-Charge.  14.1.2 With cement mortar 1:4 (1cement: 4 coarse sand)  9 Demolishing cement concrete manually/ by mechanical means including disposal of material within 50 metres lead as per direction of Engineer - in - charge.  15.2.1 Nominal concrete 1:3:6 or richer mix (including equivalent	6	13.61	Painting with synthetic enamel paint of approved brand				
7 13.80 Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete.  8 14.1 Repairs to plaster of thickness 12 mm to 20 mm in patches of area 2.5 sq.meters and under, including cutting the patch in proper shape, raking out joints and preparing and plastering the surface of the walls complete, including disposal of rubbish to the dumping ground, all complete as per direction of Engineer-in-Charge.  14.1.2 With cement mortar 1:4 (1cement: 4 coarse sand)  9 Demolishing cement concrete manually/ by mechanical means including disposal of material within 50 metres lead as per direction of Engineer - in - charge.  15.2.1 Nominal concrete 1:3:6 or richer mix (including equivalent			and manufacture to give an even shade :				
average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete.  8 14.1 Repairs to plaster of thickness 12 mm to 20 mm in patches of area 2.5 sq.meters and under, including cutting the patch in proper shape, raking out joints and preparing and plastering the surface of the walls complete, including disposal of rubbish to the dumping ground, all complete as per direction of Engineer-in-Charge.  14.1.2 With cement mortar 1:4 (1cement: 4 coarse sand) 300 Sqm 560.50 168150 means including disposal of material within 50 metres lead as per direction of Engineer - in - charge.  15.2.1 Nominal concrete 1:3:6 or richer mix (including equivalent		13.61.1	Two or more coats on new work	300	Sqm	155.90	46770
manufacturer, over the plastered wall surface to prepare the surface even and smooth complete.  8 14.1 Repairs to plaster of thickness 12 mm to 20 mm in patches of area 2.5 sq.meters and under, including cutting the patch in proper shape, raking out joints and preparing and plastering the surface of the walls complete, including disposal of rubbish to the dumping ground, all complete as per direction of Engineer-in-Charge.  14.1.2 With cement mortar 1:4 (1cement: 4 coarse sand) 300 Sqm 560.50 168150 9 15.2 Demolishing cement concrete manually/ by mechanical means including disposal of material within 50 metres lead as per direction of Engineer - in - charge.  15.2.1 Nominal concrete 1:3:6 or richer mix (including equivalent	7	13.80	Providing and applying white cement based putty of				
the surface even and smooth complete.  8 14.1 Repairs to plaster of thickness 12 mm to 20 mm in patches of area 2.5 sq.meters and under, including cutting the patch in proper shape, raking out joints and preparing and plastering the surface of the walls complete, including disposal of rubbish to the dumping ground, all complete as per direction of Engineer-in-Charge.  14.1.2 With cement mortar 1:4 (1cement: 4 coarse sand)  300 Sqm 560.50  168150  9 15.2 Demolishing cement concrete manually/ by mechanical means including disposal of material within 50 metres lead as per direction of Engineer - in - charge.  15.2.1 Nominal concrete 1:3:6 or richer mix (including equivalent			average thickness 1 mm, of approved brand and				
8 14.1 Repairs to plaster of thickness 12 mm to 20 mm in patches of area 2.5 sq.meters and under, including cutting the patch in proper shape, raking out joints and preparing and plastering the surface of the walls complete, including disposal of rubbish to the dumping ground, all complete as per direction of Engineer-in-Charge.  14.1.2 With cement mortar 1:4 (1cement: 4 coarse sand) 300 Sqm 560.50 168150 15.2 Demolishing cement concrete manually/ by mechanical means including disposal of material within 50 metres lead as per direction of Engineer - in - charge.  15.2.1 Nominal concrete 1:3:6 or richer mix (including equivalent			manufacturer, over the plastered wall surface to prepare				
of area 2.5 sq.meters and under, including cutting the patch in proper shape, raking out joints and preparing and plastering the surface of the walls complete, including disposal of rubbish to the dumping ground, all complete as per direction of Engineer-in-Charge.  14.1.2 With cement mortar 1:4 (1cement: 4 coarse sand) 300 Sqm 560.50 168150  9 15.2 Demolishing cement concrete manually/ by mechanical means including disposal of material within 50 metres lead as per direction of Engineer - in - charge.  15.2.1 Nominal concrete 1:3:6 or richer mix (including equivalent			the surface even and smooth complete.	900	Sqm	156.05	140445
patch in proper shape, raking out joints and preparing and plastering the surface of the walls complete, including disposal of rubbish to the dumping ground, all complete as per direction of Engineer-in-Charge.  14.1.2 With cement mortar 1:4 (1cement: 4 coarse sand) 300 Sqm 560.50 168150  9 15.2 Demolishing cement concrete manually/ by mechanical means including disposal of material within 50 metres lead as per direction of Engineer - in - charge.  15.2.1 Nominal concrete 1:3:6 or richer mix (including equivalent	8	14.1	Repairs to plaster of thickness 12 mm to 20 mm in patches				
plastering the surface of the walls complete, including disposal of rubbish to the dumping ground, all complete as per direction of Engineer-in-Charge.  14.1.2 With cement mortar 1:4 (1cement: 4 coarse sand) 300 Sqm 560.50 168150  9 15.2 Demolishing cement concrete manually/ by mechanical means including disposal of material within 50 metres lead as per direction of Engineer - in - charge.  15.2.1 Nominal concrete 1:3:6 or richer mix (including equivalent			of area 2.5 sq.meters and under, including cutting the				
disposal of rubbish to the dumping ground, all complete as per direction of Engineer-in-Charge.  14.1.2 With cement mortar 1:4 (1cement: 4 coarse sand) 300 Sqm 560.50 168150  9 15.2 Demolishing cement concrete manually/ by mechanical means including disposal of material within 50 metres lead as per direction of Engineer - in - charge.  15.2.1 Nominal concrete 1:3:6 or richer mix (including equivalent			patch in proper shape, raking out joints and preparing and				
per direction of Engineer-in-Charge.  14.1.2 With cement mortar 1:4 (1cement: 4 coarse sand) 300 Sqm 560.50 168150  9 15.2 Demolishing cement concrete manually/ by mechanical means including disposal of material within 50 metres lead as per direction of Engineer - in - charge.  15.2.1 Nominal concrete 1:3:6 or richer mix (including equivalent							
14.1.2 With cement mortar 1:4 (1cement: 4 coarse sand) 300 Sqm 560.50 168150  9 15.2 Demolishing cement concrete manually/ by mechanical means including disposal of material within 50 metres lead as per direction of Engineer - in - charge.  15.2.1 Nominal concrete 1:3:6 or richer mix (including equivalent			disposal of rubbish to the dumping ground, all complete as				
9 15.2 Demolishing cement concrete manually/ by mechanical means including disposal of material within 50 metres lead as per direction of Engineer - in - charge.  15.2.1 Nominal concrete 1:3:6 or richer mix (including equivalent			per direction of Engineer-in-Charge.				
means including disposal of material within 50 metres lead as per direction of Engineer - in - charge.  15.2.1 Nominal concrete 1:3:6 or richer mix (including equivalent		14.1.2	With cement mortar 1:4 (1cement: 4 coarse sand)	300	Sqm	560.50	168150
as per direction of Engineer - in - charge.  15.2.1 Nominal concrete 1:3:6 or richer mix (including equivalent	9	15.2	Demolishing cement concrete manually/ by mechanical				
15.2.1 Nominal concrete 1:3:6 or richer mix (including equivalent			means including disposal of material within 50 metres lead				
design mix)   20   cum   2434.25   48685		15.2.1	Nominal concrete 1:3:6 or richer mix (including equivalent				
			design mix)	20	cum	2434.25	48685

S.No	DSR Code	Description	Qty	unit	Rate	Amount
10	15.7	Demolishing brick work manually/ by mechanical means				
		including stacking of serviceable material and disposal of				
		unserviceable material within 50 metres lead as per				
		direction of Engineer-in-charge.				
	15.7.4	In cement mortar	10	cum	2060.20	20602
11	15.56	Dismantling old plaster or skirting raking out joints and				
		cleaning the surface for plaster including disposal of				
		rubbish to the dumping ground within 50 metres lead.	600	Sqm	54.65	32790
12	15.60	Disposal of building rubbish / malba / similar unserviceable,	3			
		dismantled or waste materials by mechanical means,				
		including loading, transporting, unloading to approved				
		municipal dumping ground or as approved by Engineer-in-				
		charge, beyond 50 m initial lead, for all leads including all				
		lifts involved.	300	cum	263.95	79185
13	17.35	Providing and fixing soil, waste and vent pipes :				
	17.35.1	100 mm dia				
	17.35.1.1	Sand cast iron S&S pipe as per IS: 1729	300	Mtr	1151.90	345570
	17.35.2	75 mm diameter :				
	17.35.2.1	Sand cast iron S&S pipe as per IS: 1729	150	Mtr	1044.75	156713
14	17.37	Providing and fixing M.S. holder-bat clamps of approved				
		design to Sand Cast iron/cast iron (spun) pipe embedded in				
		and including cement concrete blocks 10x10x10 cm of 1:2:4				
		mix (1 cement : 2 coarse sand : 4 graded stone aggregate				
		20 mm nominal size), including cost of cutting holes and				
		making good the walls etc. :				
	17.37.1	For 100 mm dia pipe	60	Each	362.85	21771
	17.37.2	For 75 mm dia pipe	60	Each	360.00	21600
15	17.38	Providing and fixing bend of required degree with access	,			
		door, insertion rubber washer 3 mm thick, bolts and nuts				
		complete.				
	17.38.1	100 mm dia				
	17.38.1.1	Sand cast iron S&S pipe as per IS: 1729	90	Each	598.50	53865
	17.38.2	75 mm dia				
		Sand cast iron S&S pipe as per IS: 1729	30	Each	501.45	15044
16	17.39	Providing and fixing plain bend of required degree				
	17.39.1	100 mm dia				
-		Sand cast iron S&S pipe as per IS: 1729	90	Each	470.45	42341
	17.39.2	75 mm dia			0=05	4.55
		Sand cast iron S&S pipe as per IS: 1729	30	Each	376.25	11288
17	17.40	Providing and fixing heel rest sanitary bend				
	17.40.1	100 mm dia			504.05	17500
		Sand cast iron S&S pipe as per IS: 1729	30	Each	584.25	17528
	17.40.2	75 mm dia	20	Fa ala	400.05	1.4702
10		Sand cast iron S&S pipe as per IS: 1729	30	Each	490.05	14702
18	17.43	Providing and fixing single equal plain junction of required				
		degree with access door, insertion rubber washer 3 mm				
	17.43.4	thick, bolts and nuts complete.				
-	17.43.1 17.43.1.1	100x100x100 mm	20	Each	726 55	1/1521
	17.43.1.1	Sand cast iron S&S pipe as per IS: 1729 75x75x75 mm	20	Each	726.55	14531
-		Sand cast iron S&S pipe as per IS: 1729	20	Each	629.50	12590
	17.43.2.1	Janu cast non 303 pipe as per 13. 1723	20	Latii	023.30	12390

S.No	DSR Code	Description	Qty	unit	Rate	Amount
19	17.60	Providing and fixing trap of self cleansing design with				
		screwed down or hinged grating with or without vent arm				
	Mr	complete, including cost of cutting and making good the				
		walls and floors :				
	17.60.1	100 mm inlet and 100 mm outlet				
	17.60.1.1	Sand cast iron S&S pipe as per IS: 1729	25	Each	1996.50	49913
	17.60.2	100 mm inlet and 75 mm outlet				
	17.60.2.1	Sand cast iron S&S pipe as per IS: 1729	25	Each	1975.15	49379
20	17.61	Cutting chases in brick masonry walls for following				
		diameter sand cast iron/ centrifugally cast (spun) iron pipes				
		and making good the same with cement concrete 1:3:6 ( 1				
		cement: 3 coarse sand: 6 graded stone aggregate 12.5 mm				
		nominal size), including necessary plaster and pointing in				
		cement mortar 1:4 (1 cement : 4 coarse sand) :	p 33			
	17.61.1	100 mm dia	50	Each	713.20	35660
21	26.4	Providing and fixing hard drawn steel wire fabric of size 75				
		x25 mm mesh or other suitable size wire mesh to be fixed				
		& firmly anchored to the concrete surface by means of "L"				
		shaped mild steel shear key welded with existing				
		reinforcement including the cost of materials, labour, tool				
		& plants as approved by Engineer-in-charge.	45	sqm	902.55	40615

TOTAL 2348008

Anurag Arora

(Manager Admin)

Prime Ministers Museum and Library

Teen Murti House New Delhi-110011